

## Laser Barcode Scanner

(Model No.: OCBS-L001)

### FEATURE:

- With best balance of quality and price
- Multiple interfaces: PS/2, RS232 and USB supported;
- Excellent decode capability,
- Durable construction combined with future-proofing;
- No extras or drivers required, plug and play design.



### SPECIFICATION:

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	80 scans per second (SPS)
Reading Distance	1 to 38cm (resolution dependent)
Scanner Type:	Bi-directional
Resolution:	0.125mm at PCS 0.9
Print Contrast Minimum:	25%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Working Way:	Triggered or automatic (continuous mode) scanning
Physical Characteristics	
Interfaces Supported:	PS/2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	150 mA
Idle Current:	<30 mA
Power Source:	Host power or external (RS232) power supply
Stand:	Optional
Dimensions:	?
Weight:	?
Color:	Gray, Black
User Environment	
Operating Temperature:	0~40 deg C
Storage Temperature:	-30~ 60 deg C
Humidity:	5~95% relative humidity, non-condensing
Drop Specifications:	Withstands multiple 1.2m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product