

Wireless Laser Barcode Scanner

(Model No.: OCBS-W001)

FEATURE:

- RF 899M Hz technology base, up to 200/100m working range;
- Protection circuit for rechargeable Lithium battery;
- Confirmation flash as receiving successfully;
- Easy programming using Windows based software;
- Multi-point operation supported.



SPECIFICATION:

Optical Performance	
Light Source:	Visible laser (670nm)
Scan Rate:	200 lines per second (SPS)
Resolution:	0.10 mm (4 mil) at PCS 0.9
Reading distance:	1-800 mm (PCS0.9)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Working Way:	Triggered or automatic (continuous mode) scanning
Physical Characteristics	
Interfaces Supported:	RS232
Power For Station:	DC 5V
Battery Type:	Rechargeable Lithium battery
Battery Capacity:	690 mh
Battery Charging Time:	2 hours
Operating Time:	8 hours
Radio Frequency:	880~899 MHz (Normal is 899 Mhz)
Radio Range:	100m and 200m optional (Antenna Built-in)
Multi-user:	Multi-point operation supported
Channels:	Up to 8 (virtual)
Dimensions:	Scanner: 18*5.5*10.5cm Station: 10*6.5*12cm (With antenna)
Weight:	Scanner:100g
User Environment	
Operating Temperature:	0~40 deg C
Storage Temperature:	-30~ 60 deg C
Humidity:	5~95% relative humidity, non-condensing
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product