

## 3 Inch Portable Mini Bluetooth Thermal Receipt Printer

(M/N:OCPP-M087)



- Support Windows, Java, Android or IOS
- Provide SDK for Android and IOS, driver for Windows PC
- Bluetooth, USB and RS232 communication
- 2000mAh high capacity battery
- Higher print speed 80mm/sec
- 50km TPH Life
- A variety of 1D and 2D code supported
- Built-in buzzer more easily for user get the printer status

| Printing        |                                 |
|-----------------|---------------------------------|
| Printing method | Direct thermal                  |
| Print width     | 72mm                            |
| Column capacity | 8dots/mm, 576dots/line          |
| Printing speed  | 80mm/s                          |
| Interface       | Bluetooth、USB、Serial            |
| Printing paper  | 79.5±0.5mm×φ40mm                |
| Line spacing    | 3.75mm (Adjustable by commands) |

## OCOM Technologies Limited

**Address:** 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

**Website:** www.ocominc.com, www.possolution.com.cn;

**E-mail:** ocom@ocominc.com;

**Tel/Fax:** +86.755.8605.3207;



|                                   |   |
|-----------------------------------|---|
| Column number                     | 58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns   |
| Character size                    | ANK , Font A : 1.5×3.0mm ( 12×24 dots ) Font B : 1.1×2.1mm ( 9×17 dots )<br>Chinese,traditional Chinese:3.0×3.0mm ( 24×24 dots )  |
| <b>Barcode Character</b>          |   |
| Extension character sheet         | PC347 ( Standard Europe ) 、 Katakana、 PC850 ( Multilingual ) 、 PC860 ( Portuguese ) 、 PC863 ( Canadian-French ) 、 PC865 ( Nordic ) 、 West Europe、 Greek、 Hebrew、 East Europe、 Iran、 WPC1252、 PC866 ( Cyrillic#2 ) 、 PC852 ( Latin2 ) 、 PC858、 IranII、 Latvian、 Arabic、 PT151 ( 1251 ) |
| Barcode types                     | UPC-A/UPC-E/JAN13 ( EAN13 ) /JAN8 ( EAN8 )<br>/CODE39/ITF/CODABAR/CODE93/CODE128/QR/PDF417  |
| <b>Buffer</b>                     |   |
| Input buffer                      | 32k bytes   |
| NV Flash                          | 64k bytes   |
| <b>Power</b>                      |   |
| Power supply                      | Input : AC 110V/240V, 50 ~ 60Hz   |
| Power source                      | Output : DC 9V-2A   |
| <b>Physical characteristics</b>   |   |
| Weight                            | 0.19KG  |
| Dimensions                        | 111×88×41mm(D x W x H)  |
| <b>Environmental Requirements</b> |   |
| Work environment                  | Temperature (0 ~ 45) humidity(10 ~ 90%)   |
| Storage environment               | Temperature(-10 ~ 60℃) humidity(10 ~ 90%)   |
| <b>Reliability</b>                |   |

## OCOM Technologies Limited

**Address:** 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

**Website:** [www.ocominc.com](http://www.ocominc.com), [www.possolution.com.cn](http://www.possolution.com.cn);

**E-mail:** [ocom@ocominc.com](mailto:ocom@ocominc.com);

**Tel/Fax:** +86.755.8605.3207;



---

|                   |      |
|-------------------|------|
| Printer head life | 50KM |
|-------------------|------|