

# بو عالية السرعة 80 ملليمتر الحرارية استلام الطابعة بلوتوث + أوسب الموائى-Aأوكب-88

(88-0000 :0000 000000A)



00000:

1. 000000 0000 00 0000 0000
2. 0000000 / 00000000 300 000 000 00000000 000000.
3. 000000 000000000 00000000.
4. 000000000 00000000000 00000000000 000000
5. 0000 + 0000000 000000 + 000 000 0000 + 00000000 + 0000 000000 :00000000 0000000 0000000
6. 0000000 0000000 0000000 000 000000 00000000 0000000.
7. 1 0000000 000d 0000000000 000000 0000 00 0
8. 000000000 00000000 00000 0000
9. 00000000 0000 0 0000000000 00.
10. 100 00 000000000 0000 0000000km 000000000
11. 00000000 0000 / 00000 00000000 00 00000000.

000000000:

00000000 000000	0000000000 00000000 00
00000000 000000	576dots / 512 0(00000000) 0000dots / 0000 24 00000000 00000000 :000000000x24 00000000 0000 000000 000000 18030 0000 000000 0000000000 000 0(00000000 00000) 00000000000 00000 0000000.
00000	a: 12 * 24dots 1.5 (w) * 3.0 (h) 000 b: 9 * 17dots 1.1 (w) * 2.1 (h) 00 24 * 24 :00000000000 / 000000000dots 3.0 (W) * 3.0 (H) 00
0000000000 0000	00000-A / 00000-E / JAN13 (EAN13) / JAN8 (EAN8) / 00000 / 000000000 / CODE39 / CODE93 / CODE128 000000000 0000000000 0000
000000000 00000	250MM / 300 000000000 000000 0000000 000000MM / 00000000 00000 00000 000000
000000 0000	00000 + 00000000 000000 + 000 000 0000 + 000000000 + 0000 000000
000000000 0000	000000000 0000 / 00000 00000000 00 00000000
00000000000	Win9X / 00 000000 / win2000 / win2003 / 8 0000 / 7 0000 / 000000 0000 / win8.1 / 000000000 0000 0 0000000000 00 00000000 00 00000000 00000000.
000000 0000	79.5 ± 0.5mm (72 000000000 0000mm)
000000 0000	83mm
0000 00000	0.06-0.08mm
0000000	000000000) 00000000000 0000)

OCPP-88A-U	100KM
OCPP-88A-URL	DC24V / 2.5A
OCPP-88A-W	0-45
OCPP-88A-BU	10-80
OCPP-88A-U0	190 * 145 * 145 (mm)
OCPP-88A-URL0	1.60kg
OCPP-88A-W0	P / N
OCPP-88A-BU0	OCPP-88A-U
	OCPP-88A-URL
	OCPP-88A-W
	OCPP-88A-BU
	OCPP-88A-U0
	OCPP-88A-URL0
	OCPP-88A-W0
	OCPP-88A-BU0

OCPP-88A-U: 100KM



OCPP-88A-URL: DC24V / 2.5A



80mm OCPP-88A-W: 0-45mm OCPP-88A-BU: 10-80mm OCPP-88A-U0: 190 \* 145 \* 145 (mm) OCPP-88A-URL0: 1.60kg OCPP-88A-W0: P / N OCPP-88A-BU0: OCPP-88A-U OCPP-88A-URL OCPP-88A-W OCPP-88A-BU OCPP-88A-U0 OCPP-88A-URL0 OCPP-88A-W0 OCPP-88A-BU0