

وطابعة بلوتوث تاكسي الكمال تصميم الروبوت المدعومة 58mm مصغرة OCPP-M03 (نموذج)

المواصفات:

البعض الكل (W × D × H)	105 × 75 × 45MM
الوزن	134g
اللون	الأسود
عرض الطياعة فعالة	48MM
طريقة الطياعة	خط الطياعة الحرارية
أوامر الطياعة	مجموعة الأوامر متوافقة ESC / POS
سرعة الطياعة	ثانية / mm حتى ضربات 90
قرار	نقطة / مم (8 203) DPI
الخط طباعة	12X24 / 24X24
قدرة العمود	32 16 columns الأعمدة /
حجم الحرف	1.5 × 3.0 mm (W×H) / 3.0x3.0mm (WXH)
أبعاد الورق	58.0 ± 0.1MM × 40.0 mm
سمك الورق	0.06 mm إلى 0.08 mm
مجموعة الأحرف	أبجدية / الصينية كانجي
واجهة	(وقنية بلوتوث اختياري، USB, RS-232,
فلاش	256KB
محول الطاقة	9V DC / 2A
طاقة البطارية	و. البطارية تستطيع البقاء بفضل 4-5 أيام، وعندما يكون السلطة 7.4V DC / 1500mA المكاملة، ويمكن طباعة الورق 150-120m
ميزات أخرى	كشف الورق، والكشف عن السلطة، دليل إغلاق
ظروف العمل	% الرطوبة: 10 ~ 90°C درجة الحرارة: -10 ~ 20 درجة
ظروف التخزين	% الرطوبة: 5 ~ 95°C درجة الحرارة: -20 ~ 70 درجة
اسم الجهاز	ASCII يمكن تخصيص، رسالة والرقمية للخيارات، في حد أقصى 30 حرفا.
كلمة المرور	أدخل الرمز الافتراضي الافتراضي "1234" ، يمكن تخصيص. في أقصى 6 الرقمية.
البعض قابس الطاقة	3.5 * 1.1mm



58mm Bluetooth Thermal Printer for Andorid or IOS system

OCPP-M03



Product Picture





Features

Simple but not easy

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec



Support Windows,Android, or iPhone OS;
Bluetooth, USB and RS232 communication



Higher print speed 90mm/sec.
100km TPH Life

Low power consumption and large capacity Lithium battery.



III All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm



Parameter

Overall Dimension (W×D×H)	105×75×45mm
Weight	134g
Color	Black
Effective print width	48mm
Print method	Thermal line printing
Print commands	ESC/POS compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	32 columns/ 16columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions	58.0±0.1mm x diameter 40.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji
Interface	USB, RS-232, Bluetooth (optional)
Flash	256KB
Power Adapter	9V DC/2A

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

III | Shipping and payment

1. EXPRESS: around 3-7 working days to arrive
2. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
3. By sea: depend on which destination port
4. T/T
5. Western Union
6. Escrow
7. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

