

CCD

OCBS -B240

628nm CCD

150

2M 10,000

HID& SPP

Micro USB

&

	-60m 20m
	3.0
	Apple IOS Android XP Win7
	8KB
	/ /
	CCD
	LED 622nm-628nm
	300 /
	5MIL PCS = 0.9 Code 39
	2500
	40nm 430nm
BER	1/500
	+ 30 60 65;
	UPC-A UPC-E EAN-8 EAN-13 EAN-14; UCC / EAN 128 Code 128 Code 39 Code 39 Full ASCII; Codabar / NW7 Code 93 Code 11 MSI / PLESSEY UK / PLESSEY; Interleaved 2 of 5 Industrial 2 of 5 Standard 2 of 5 Bearer 2 of 5; Matrix 2 of 5 Deutsche 14 Deutsche 12; Bookland CIP Code DUN 14 ITF 14 Pos t ITF 16 ITF 6; LOGMARS ISBN ISSN ISBT IMEI Canadian Customs; GS1 Databar RSS
	USB
	100mm * 45mm * 20mm * * *
	69.8
	2
	ABS + PC
	100mA 45Ma 1mA
	DC3.3V 0.33W
	LED

□□□□	
□□□□	-20°C□+ 60°C
□□□□	-40°C□+ 85°C
□□	5□~95□□□□□□
□□□□	0□100000lux
□□	□□□□
□□□□	FCC B□CE EMC B□



□□□□

□□□□