

4

M / N OCBP -004A / B

8 MB SDRAM 200 Mhz 32 RISC 4 MB

127 5

300 984' 25.4 1

Kiosk

TSPL-EZ™ TPLE TPLZ

	OCBP -004A	OCBP -004B
	8 / mm 203 DPI	12 / mm 300 DPI
	127 5	101.6 4
	104 4.25	104 4.09
	2794 110	1016 40
	20-112mm 0.78"-4.4"	
	0.06~0.254 mm 2.36~10 mil	
	10~2,794 0.39"~110"	10~1016 0.39"~40"
	127 5	
	300 67 mm 1" 40 mm~110 mm 1.6"~4.3"	
	234 x 194.8 x 302.5	
	3.1 6.83	
	32 RISC CPU	
	4MB Flash Memory	
	8MB SDRAM	
	SD 4 GB	
	<ul style="list-style-type: none"> •USB2.0 •RS-232 •Centronics •10/100 Mbps •802.11 b / g / n 	
	AC 100-240V 1A 50-60Hz	
	DC 24V 2.5A 60W	
LED	1 1 1 LED 3	

□□□	□□□□□□□□ position□□□
	□□□□□□□
	□□□□□□□
	□□□□□□□
□□□□	□□
□□□□	8□□□□□□□□□□ □□TTF□□□□
□□	1D□□□Code 39□Code 93□Code 128UCC□Code 128□A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□ EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□MSI□PLESSEY□POS TNET□□□POS T □□□□□PDF-417□Maxicode□DataMatrix□□□□□
□□	BIMAP□BMP□PCX□□□256□□
□□□□□□□□	0°□90°□180°□270°
□□□□□□	TSPL□EPL□ZPL□DPL□
□□□□	□□□5~40°C□25~85□□□□□ □□□-40~60°C□10~90□□□□□
□□□□	FCC□CE□CCC□CB
□□□□	□□RoHS
□□	①Windows□□□□CD□;②□□□□□□;③USB□□;④□□□□; ⑤□□□□□□□□□;⑥□□□□□□□□x 2,1.5"□□□□x 2; ⑦Ribbon□□x 2;⑧Ribbon□□;⑨□□
□□□□	□□□□□□10/100 Mbps□RS-232□Centronics□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□0.06~0.19mm□ □□500000; 0.20~0.25mm□□□20□
□□□□	□□□□□□□□□OD□ 214□□□8.4□□□□25.4□□□1□□□□□□□□□□□□ □□□□□□□□□□802.11 b / g / n□□□□□□□□□□□□□□□□RFID□□□□

Product show:



□□□□□

OCOM.com