

OCBP-004B-L 300DPI

M / N OCBP-004B-L

1

8 MB SDRAM 200 Mhz 32 RISC
 4 MB
 127 5
 300 984 25.4 1
 TSPL-EZ™ TPLE TPLZ

2. Parameters

| | OCBP-004A | OCBP-004B |
|--|---|-----------------|
| | 8 / mm 203 DPI | 12 / mm 300 DPI |
| | & | |
| | 127 / s | 101.6 4 / s |
| | 108 4.25 | 104 4 09 |
| | 2794 110 | 1016 40 |
| | 20-112mm 0.78"-4.4" | |
| | 0.06 0 254 2.36 10 | |
| | 10 2 794 0 39 110 | 10 1016 0 39 40 |
| | 127 5 | |
| | 300 67 1 40 110 1.6 4.3 | |
| | 234 w ^ X194.8 H x 302.5 d | |
| | 3.1 6.83 | |
| | 32 RISC CPU | |
| | 4MB | |
| | 8MB SDRAM | |
| | SD 4 GB | |
| | • USB2.0 • RS-232 • Centronics • 10/100 Mbps | |
| | • 802.11 b / g / n | |
| | AC 100-240V 1A 50-60Hz | |
| | DC 24V 2.5A 60W | |
| | 1 1 LED 3 | |
| | | |
| | | |
| | | |
| | 8 | |
| | TTF | |
| | EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 39 93 128 UCC 128 A B C Codabar 2 5 MSI PLESSEY POSTNET PDF-417 Maxicode DataMatrix QR BIMAP BMP PCX 256 0° 90° 180° 270° TSPL EPL ZPL DPL 5 40°C 25 85 -40 60°C 10 90 FCC CE CCC CB RoHS | |

Harold Hu

OCOM

104518054

www.ocominc.com www.possolution.com.cn;

sales14@ocominc.com;

Skype [sales14@ocominc.com](https://www.skype.com/people/sales14@ocominc.com)

MSN ocomsales14@hotmail.com;

Whatsapp 86.18948789890;

18948789890@ocomsales14;

86.18948789890;

QQ 1467261417;

0086.755.86053207-814;

0086.755.86053207-868;