

3

M / N OCBP -015

- 8
- TSPL ECS / POS
-
- 1D 2D
-
- 100M
- 2MB DRAM 2MB
- 25 80mm
- 150

	TSPL ECS / POS	
	203dpi 576dots / line.	
	max = 72mm.	
	R.eceipt	
	SB./UL./URL./ U.+ Bt./ U + WiFi / URL + BT / URL + WiFi	
	= 152mm / s 260mm / s	
	20mm-80	
	0.06 0.19	
	Ø83	
DRAM	2MB.	
Flash	2MB.	
	A 12 * 24 B 9 * 17	
	GB18030 Big5 24x24dots	
	PC347 PC850 PC860 PC863 PC865 WPC1252 PC866 2	
	PC852	
	PC858 PT151 1251	
1D	UPC-A / UPC-E / JAN13 / Jan8. / code39 / ITF / Codabar / Code93 / Code128/ MSI / ITF-14 / C POS T / PLESSEE	
2D	QR. pdf417 dm	
	15.0	
	AC 100V-240V 50 / 60Hz	
	DC 24V / 2.5A	
	0°C 45°C 10 80 RH	
	-10°C -60°C 10 90 RH	
	196 d x 145 w x 135 h mm	
	1.14kg.	
	1.5kg.	
	30x19x18cm l x w x h	1Unit /
	62x36x52cm l x w x h	12 /
	Windows XP / Vista / Win7 / Win8 / Win10 / Win 2000 / Win CE / O POS / J POS	
SDK.	Android iOS.	



OCBP-015





OCBP-015





OCBP-015





OCBP-015





OCBP-015







□□□□

OCOM□□□□□□□□□□