

OCBS-2099

OCBS-2099)

OCBS



OCBS

1MP 1MP(1280*800)

OCBS

OCBS

OCBS

400

OCBS

OCBS

	OCBS-2099
	ABSPC
	耗電量 < 280 mA 待機耗電量 < 130 mA
	5 英寸 (-10%)/500 英寸
	1.2GHz
	RS-232; USB 或 USB 或 POS 或
	LED 及
	CMOS 1280*800 英寸
	LED
	4mil
	8KV
	厚度 1.2mm
	≥15%
	GS1 DataBar™ 或 GS1 DataBar Expanded Stacked 或 GS1 DataBar 或 GS1 DataBar 或 GS1 DataBar PDF417 或 PDF417
	尺寸 334 英寸 39 60mm—160mm 334 英寸 EAN-13 90mm—150mm 5mil CODE39 70mm—240mm 5mil EAN-13 70mm—230mm 1300 英寸 UPC-A 40mm—450mm 5mil PDF417 65mm—210mm 5mil QR 75mm—140mm 1000 英寸 QR 45mm—290mm 1000 英寸 30mm—260mm 2000 英寸 QR 20mm—480mm 或
	傾斜 0-360° 或 ±60° 或 ±60°
	重量 300g
	172*67*87mm

□□□	175*110*80mm
20□1□□	420*370*237mm/7.0kg
□□	
□□□□□	0□45□□□□10%~80% □□□
□□□□□	-20 □ 60 □□□□10%~90% □□□











