

□□□

200scan/sec □□□□□□□□□□

□□□□□□□

□□ KBW□RS232 □ USB

□□□□□□□□□□□□

□□□□□□□□□□

□□□

□□□	OCBS-LA09
□□	ABS+PC
□□	□□□
□□	□
□□	PS2□RS232□USB □□
□□	□□□□LED
□□□□□	32 □
□□□□	□□□□
□□	5V DC±5%
□□□	85 □□□□□□□100□□□□
□□□□	□□+/-15KV□□□□□+/-8KV□□□□
□□□□	□□□□ 1.5m □□□□□□□□
□□□□	EN60825-1□1□
□□	
□□□□	□□ 200 □□□
□□□□	2.5~600mm (100% UPC/EAN)
□□□□	50mm@60mm, 220mm@200mm
□□□□□	□□
□□□	3mil□□□□□□□/5mil□□□□□
□□□□	0 ~ 100,000 □□□
□□□□□	25%
□□	650nm □□□
□□□□	±65°□□□□□±60°□□□□□±42°□□□□
□□□□	UPC/EAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Coda bar, Interleaved 2 of 5, Discrete 2 of 5, Code 93 , MSI, Code 11, RSS □□, Chinese 2 of 5 , MSI/Plessey , UK/Plessey , UCC/EAN 128 , Chinese code , GS1 Data Bar □RSS □□□
□□□□	
□□	□□□550g
□□	230*140*10mm
20 □ 1 □	480 * 240 * 550mm/12.25kg
□□	
□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□	-20 □ 60□□□ □10%~90% □□□









