

2D

M / N OCBS -T214

;
1D / 2D;
;

	OCBS -T214
	USB
	5V.
	380mA.
	240mA.
	190mA.
	8g r.m.s. 10 500 Hz 2 3
	CMOS
	LED
	44°h 34°v
	> 0.4m / s
	±65°@ 0°0° 360°@ 0°0° ±65°@ 0°0°
	20
	0-100,000Lux
	Code39 5MIL 0mm-120mm Code39 13mil 0mm-240mm QR 20mil 0mm-210mm QR 3 * 3cm 40mm-650mm QR 2.3 * 2.3cm 20mm-550mm

□□□□	1D□Code128 / EAN128□EAN.CCCOM pos ITE□ Interleaved2of 5□RSS□Pos TNET□Plessey□□□□□39□Codabar□□□93□ □□11□Telepen□MSICODE□□□2□5□UPC / EAN□ 2D□PDF417□QR□□5□5□MicroPDF417□□□□□Pos T□□□□Pos T□□□□Pos T□Maxicode□Codablock□Aztec□Dutch Pos T□TLC 39□Datamatrix□
□□	
□□	□□□437g
□□	151 * 142 * 84mm
□□	
□□□□□□	0□45□□□□10□□80□□□□□
□□□□□□	-20□60□□□□10□□90□□□□□





OCBS-T214





OCBS-T214





OCBS-T214





Relevant documents:

[OCBS-T214 user manual](#)