

15.6 15.1 Andorid/Windows POS

(M/N POS-G156/G151)

OCOM G POS IO



I3 I5

Rockchip RK3288

EMMC 8GB/16GB/32GB

MSATA SSD 64GB SSD 128GB 256GB

58mm 80mm

MSR VFD220

| | |
|----------------------|--|
| POS-G156W/A | |
| 15.6寸 POS | |
| | |
| | |
| | |
| 15.6寸 | |
| 1366*768 | |
| 250cd/m ² | |
| 160度 150度 | |
| GG | |
| 15.6寸 13.3寸 1366*768 | |
| 2*20 VFD | |
| | |
| Windows | Intel Celeron J4125, 2.0GHz / intel core I3 / I5 4th CPU |
| | 1*SO-DIMM DDR4 2400mHZ 4GB 8GB |
| | Msata SSD 64GB 256GB |
| | Real Tek ALC662 |
| | 10/100Mbs Realtek RTL8111F Mini PCI-E WIFI |
| | Windows 10/11 |
| | Rockchip RK3568 RK3288 RK3399 |
| | DDRIV 2GB 4GB |
| | 16GB EMMC 32GB |
| | RJ45 10/100Mbs |
| | WIFI & BT Wi-Fi 802.11b/g/n BT3.0/BT4.0 |
| | Android 7.1 Android 8.1 Android 11 |
| | |

| | |
|----------------------------------|---------------------|
| Windows Android(J4125&RK3568) | WiFi*1 |
| | 12V DC 5V *1 |
| | RS232 *1 |
| | RJ-45 *1 |
| | USB*5 |
| Windows (J4125) | WiFi*1 |
| | VGA(15pin D-sub) *1 |
| | RJ11 *1 |
| | PS/2 *1 |
| RK3568 | RJ11*1 |
| | TF*1 |
| 80mm/s | 150mm/s |
| | 79.5- / 0.5mm |
| | 100km |
| | USB |
| | LPT |
| 58mm/s | 80mm/s |
| | 57.5- / 0.5mm |
| | 50km |
| | LPT |
| | MSR |
| MSR | |
| 80hm/5W | |
| 6.5Kg | |
| 15.6 | |
| 8.5Kg | |
| 300*465*500 | |
| 0~40 | |
| -10~60 | |
| 10%~80% | |
| 10%~90% | |
| 110-240V/50-60HZ | |
| DC12/5A | |
| DC12V/7A | |
| FCC A | |
| CE | |
| LVD | |
| CCC | |

All In One Touch Screen POS System




Product Display

The whole machine featured anti-static protection, anti-surge, ESD, anti-interference, anti-ESD up to 10KV.



Accessories




Product Accessories


SUPPORT SYSTEMS



Product Interface



Screen Size



Product Color



Product Details



□□



□□□□

[POS-G15 Windows SDK](#)

[POS-G15 Android SDK](#)

[POS-G15□□80□□□□□□](#)