

# Mini beweglicher androider magnetischer Streifen-Kartenleser (Modell: CR1300)

## Technische Daten:

Dimension	90 mm (L) · 26 mm (B) · 28 mm (H)		
Gewicht	85 g (ca.)		
Power Liefern	+ 5V DV ± 5%		
Power Verbrauch	40mA (Max.)		
Betrieb Ort	Innenbereich benutzen		
Karte Standard	ISO7811 / 7812		
Verfolgen Position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINTS)
Aufnahme Dichte	210 BPI	75 BPI	210 BPI
Aufnahme Kapazität	79 Zeichen (7bits)	40 Zeichen (5bits)	107 Zeichen (5bits)
Schnittstelle	USB / Seriell		
Karte Dicke	Kunststoff 0,76 ± 0,08 mm		
Kopf Funktion	Lesen Nur 1,5 mm		
Betrieb Geschwindigkeit	10 ~ 150 cm / Sek		
Leben Des Kopfes	500.000 Kartenausweise (1 Durchgang: 1 Streich)		
Fehler Preis	Weniger Als 0,5% (JSE Testkarte)		
Temperatur	Lagerung: -30 ° C bis + 70 ° C Betrieb: -20 ° C bis + 70 ° C		
Feuchtigkeit	Lagerung: 0% bis 95% RH Betrieb: 20% bis 90% RH		

## Produktdetails:



# Mini Magnetic Stripe Card Reader

CR1300



Product Picture





## Features

### **Simple but not easy**

Mini reading magnetic stripe card  
Compatible with Android System;





All 3 tracks can set to 75/210 BPI;

Long service life (500,000 card passes);



USB or Serial interface;

Suitable for all ISO7811/7812,  
ANSI, AAMVA and CA DMV  
magnetic cards;



## All-round show





## Application Area

- Financial Banking: Credit Card, Debit Card, Bank Card
- Retail: Gift Card, Customer ID, Store ID
- Government: Driver License, Health Card, Government ID
- Any movable data collection Trade shows, Racing events
- Employee's Time / Attendance data collection
- Exhibition visitors' data collection, Conference attendants data collection
- Card Verification: Age verification
- Point of Sales: Payment collection, Credit card data collection
- Law Enforcement: DMV card
- Attendance: Student ID, Membership Card, Club ID



## Parameter

Dimension	90mm(L) x 26mm(W) x 28mm(H)		
Weight	85g(approx.)		
Power Supply	+5V DV $\pm$ 5%		
Power consumption	40mA (max.)		
Operation Locus	Indoor use		
Card Standard	ISO7811/7812		
Track Position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINTS)
Recording Density	210 BPI	75 BPI	210 BPI
Recording Capacity	79 Characters (7bits)	40 Characters (5bits)	107 Characters (5bits)
Interface	USB / Serial		
Card Thickness	Plastic 0.76 $\pm$ 0.08mm		
Head Function	Read only 1.5mm		
Operation Speed	10 ~ 150cm/sec		
Life of Head	500,000 card passes (1 pass : one swipe)		
Error Rate	Less than 0.5% (JSE Test card)		
Temperature	Storage : -30°C to +70°C Operating : -20°C to +70°C		
Humidity	Storage : 0% to 95% RH Operating : 20% to 90% RH		

## Production Line





## Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ Indicates information has been verified onsite by IUV on 2013.7.15

## Quality Assurance



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

## Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No information	13

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Certifications



## Packing and Shipment



## Payment



## Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



## Why you choose us?



## Company Profile

This Assessed Supplier Has Been  
**Independently Verified**

Build Your Growth On Trust



**TÜVRheinland**<sup>®</sup>  
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of leading suppliers of POS and Auto-ID related products from China.



OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

### Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: [ocom@ocominc.com](mailto:ocom@ocominc.com) , [ocomtech@gmail.com](mailto:ocomtech@gmail.com) ;

Skype: ocominc2000, ocominc;

MSN: [ocomtech@hotmail.com](mailto:ocomtech@hotmail.com), [ocominc@hotmail.com](mailto:ocominc@hotmail.com);

Trademanager: [szocominc, cn1500439666](https://www.trademanager.com/cn1500439666);

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



**Relevante Dokumente:**

Möchten Sie mehr infOrmationBitte Klick hier.

[Spezifikation](#)

[Handbuch](#)

[SDK](#)

[Werkzeuge](#)