

433Mhz oder Bluetooth Wireless 2D Barcode Scanner Lieferant in China

Eigenschaften:

- 1.433Mhz drahtlose Kommunikation Abstand im Freien 300m, Innen 100m; Bluetooth drahtlose Kommunikation Abstand im Freien 20m und 10m Innen;
- 2.Equipped mit Kommunikation und Aufladung Unterseite
- 3.Soft Plastikabdeckung, zum des Objektivs zu schützen und Umriss stark erhöht die Anti-Tropfen-Leistung;
- 4.Barcode auf Computern und Handys Bildschirm kann gescannt werden;
5. Kein Fahrer, Plug-and-Play;
- 6.Can speichern mehr als 10.000 Stück Daten;
- 7.Mehrere Scanner können an einen Empfänger angeschlossen werden (433mhz).

Parameter:

Ziel Lichtquelle	617 nm LED
Licht Lichtquelle	625 nm LED
Abtastwinkel	39 ° (H) x 25 ° (V)
Drehwinkel	0 - 360 °
Höhenwinkel	± 65 °
Neigungswinkel	± 60 °
Kontrast drucken	Höher als 25%
1D	UPC / EAN, UPC / EAN mit Ergänzungen, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 Von 5, Interleaved 2 von 5, Discrete 2of 5, Codabar, MSI, Chinesisch 2 von 5, GS1 Data Barvariants, Koreanisch 3 von 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Datenmatrix, Maxicode, QR Code, MicroQR, Aztec
Schnittstelle	USB (Wireless Empfängerkabel)
Kommunikationsabstand	433mhz: Innen: 100m; Außen: 300m (Max) Bluetooth: Innen: 10m; Außen: 20m (Max)
Betriebstemperatur	-10 ° C - 45 ° C
Lagertemperatur	-20 ° C - 65 ° C
Betriebsfeuchtigkeit	5% -85%
Lagerfeuchtigkeit	5% -95%
Haltbarkeit	Widersteht mehrfachen 1,5m Tropfen zu Beton
Eingangsleistung	DC 5V, 280mA
Ladezeit	6h
Batterie	1500mAh
Lumination	Innen: 3.000 LUX max; Außen Sonnenlicht: 86000LUX max
IP Grade	IP42
DECODE RANGES	

Typische Leistung *		Typische Arbeitsbereiche	
		HD-Fokusbereich	
Barcode-Typ	Symbol Dichte	In der Nähe von	Weit
Code 39	5,0 mil	5mm	90mm
100% UPCA	13,0 mil	8mm	200mm
Code 39	20,0 mil	8mm	250mm
PDF 417	6,8 mil	5mm	95mm
Datenmatrix	10,0 mil	5mm	110mm
QR-Code	20,0 mil	10mm	150mm
Auflösung 1D Code 39	4 mil		
Auflösung 2D Datenmatrix	10 mil		
Material	ABS + PC		
Dimension	Scanner (70 * 95 * 168mm) Sockel (145 * 112 * 74mm)		
Nettogewicht	Scanner 185g Basis 186g		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT
INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

