

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



80MM Thermal Printer with Auto Cutter

(Model NO.: OCPP-80K)

Features:

- ◆ Support 8 kinds abundant interface combination
- ◆ Supports multi 1D barcode and QR code printing.
- ◆ Support printer status monitoring function
- ◆ Support printing queuing ticket function
- ◆ 100M Ethernet port, ultra high speed data transmission.
- ◆ 256KB NV Logo storage and 256kb big buffer memory.
- ◆ 48to80mm adjustable Paper separator for optional
- ◆ Compatible with OPOS/JPOS driver.
- ◆ 100KM long life printer head



Technical parameters :

Print Method	Direct Thermal
Command	ESC/POS
Resolution	576dots/line or 512dots/line
Printing Width	Max=72mm
Paper Type	Thermal Receipt Paper
Interface	USB/UR/UL/URL/U+BT/ U+WIFI/URL+BT/URL+WIFI
Print Speed	200mm/s (U/UR) 230mm/s (UL) 260mm/s (U+BT/ U+WIFI/ URL/ URL+BT/ URL+WIFI)
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.06~0.08mm
Roll Dia	Max. Ø 83 mm
Paper Cut	Manual tear and Auto-cutter
Input buffer	256kbytes
NV Flash	256kbytes
Font Size	font A:12*24(standard), font B:9*17
Chinese	GB18030,BIG5 24x24dots
Japanese/Korea	Support

Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



User-defined language	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect.		
1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128		
2D	QR code (Single USB or UR solution no QR code function)		
Printing head life	100 KM		
Cutter life	1million		
Paper separator	Optional		
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)		
Input	AC 100V-240V 50/60HZ		
Output	DC 24V/2.5A		
Working Condition	0°C~45°C, 10%~80%RH		
Storage Condition	-10°C-60°C,10%~90%RH		
Accessories	Data cable,power adaptor,power code,paper roller,CD>manual, (standard) Paper separator(option)		
Dimensions	196(D)x145(W)x135(H)mm		
Net weight	1.14kg		
Gross weight	1.5kg		
Individual box	Dimension	30X19X18cm(LXWXH)	1unit/carton
Master carton	Dimension	62X36X52cm(LXWXH)	12units/carton
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS		
SDK	Android, IOS		

Product specifications are subject to change without prior notice.

Together We Quest For The Best