

# Portátil Wireless Barcode Scanner

## (Modelo:OCBS-W700)

### ESPECIFICACIONES:

| Characterstics FÍSICAS            |   |
|-----------------------------------|---|
| Fuente de luz:                    | Visible láser rojo de 650 nm  |
| Dimensiones del scanner:          | 160mm * 70mm * 40m m(W * H * D)   |
| Peso:                             | 300G  |
| Material:                         | ABS + PC  |
| Modo de escaneo:                  | Un análisis de la línea; Manual / Automático  |
| Indicador Way:                    | Zumbador y luz indicadora   |
| Characterstics RENDIMIENTO        |   |
| Ancho de campo:                   | 20mm @ escáner ventana<br>260 mm @ 260 mm   |
| Profundidad de campo:             | 4mil (0.1mm) / 5-60mm<br>5mil (0.12mm) / 10-100mm<br>10mil (0.25mm) / 15-250mm<br>35mil (0.89mm) / 140-600mm<br>43mil (1.1mm) / 150-800mm |
| Velocidad de escaneo:             | 120 lecturas / seg  |
| Precision Scan:                   | 0.10mm (pcs0.9)   |
| Contraste de impresión:           | Mínimo 30% de diferencia reflexión  |
| Tasa de error:                    | 1 / (6 millones)  |
| Capacidad de decodificación:      | Códigos de barras 1D internacionales generales  |
| Actual:                           | 60 mA (de trabajo); □5uA (en espera)  |
| Escaneo Corner:                   | 32 °  |
| Escaneo Elevación:                | 68 °  |
| Escaneo ángulo de Avertence:      | 52 °  |
| Frecuencia de trabajo:            | 2.4GHz  |
| Distancia de comunicación:        | 100m (Lugares abiertos)<br>20m (de interior)  |
| Interfaz de comunicación:         | USB   |
| Characterstics entorno de usuario |   |
| Especificación de caída:          | 2m caída libre  |
| Nivel láser:                      | Nivel-1 estándar de seguridad del láser   |
| Cargue de energía:                | Corriente continua5V  |

### Detalles del producto:



**Wireless Barcode Scanner**

**OCPP-W700**

**Product Picture**





## Features

### Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);



Outside communication distance can



reach 100m, inside is 20m;;

20 scanners can work in the same field without interfering each other;



Plug and play;



800mA big capacity Li-battery.



### ||| All-round show





## Parameter

| PHYSICAL CHARACTERISTICS      |   |
|-------------------------------|---|
| Light Source                  | Visible Red Laser 650 nm  |
| Scanner Dimensions(W * H * D) | 160mm * 70mm * 40mm   |
| Weight                        | 300G  |
| Material                      | ABS + PC  |
| Scanning Mode                 | One line scanning; Manual / Automatic   |
| Indicator Way                 | Buzzer and Indicator Light  |
| PERFORMANCE CHARACTERISTICS   |   |
| Width of Scan Field           | 20mm@scanner window<br>260mm@260mm  |
| Depth of Scan Field           | 4mil (0.1mm)/5-60mm<br>5mil (0.12mm)/10-100mm<br>10mil (0.25mm)/15-250mm<br>35mil (0.89mm)/140-600mm<br>43mil (1.1mm)/150-800mm |

|   |                                     |
|---|-------------------------------------|
| Scan Speed                              | 120 scans/sec                       |
| Scan Precision                          | 0.10mm (pcs0.9)                     |
| Printing Contrast                       | Minimum 30% reflection difference   |
| Error Rate                              | 1/(6million)                        |
| Decode Capability                       | International general 1D barcodes   |
| Current                                 | 60mA (working); $\leq$ 5uA(standby) |
| Scanning Corner                         | 32°                                 |
| Scanning Elevation                      | 68°                                 |
| Scanning Angle of Avertence             | 52°                                 |
| Working Frequency                       | 2.4GHz                              |
| Communication Distance                  | 100m (Open Places)<br>20m (Indoor)  |
| Communication Interface                 | USB                                 |
| <b>USER ENVIRONMENT CHARACTERISTICS</b> |                                     |
| Drop Specification                      | 2m free fall                        |
| Laser Level                             | Level-1 laser safety standard       |
| Charge Power                            | 5VDC                                |

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



© 2012-2013 All rights reserved. www.coming.com





OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.



## Documentos pertinentes:

¿Quieres saber más inf productormación?Por favor, Haga clic aquí.

[Especificación](#)