

Auto Sense Handheld Laser Barcode Scanner con soporte
(Modelo: OCBS - L012)

PRESUPUESTO:

Características de presentación	
Fuente de luz:	Láser visible (650-670nm)
Rango de escaneo:	100 escaneos por segundo
Distancia de lectura	2.5 ~ 600 mm (100% UPC / EAN)
Tipo de escáner:	Bi-direccional
Resolución:	0.10mm (4mil) en PCS 0.9
Mínimo de contraste de impresión:	30%, diferencia mínima de reflexión (@ 650nm)
Tasa de error:	1/3000000
Capacidad de decodificación:	UPC / EAN, UPC / EAN con suplementarios, UCC / EAN128, código 39, código 39 ASCII completo, código 39 trióptico, código 128, código 128 ASCII completo, codabar, intercalado 2 de 5, discreto 2 de 5, código 93, MSI , código 11, ATA, variantes de RSS, chino 2 de 5 ...
Características físicas	
Interfaces compatibles:	PS2, RS232, USB
Voltaje:	DC + 5V +/- 5%
Corriente:	100 mA
Corriente de reposo:	& lt; 40 mA
Fuente de alimentación:	Fuente de alimentación principal o externa (RS232)
Ángulo de escaneo	Inclinación 45 ° Elevación 60 °
Dimensiones:	L165mm X W63mm X H87mm
Peso:	129g (sin soporte)
Estar	Opcional
Color:	Gris y negro
Entorno de usuario	
Temperatura de funcionamiento:	0 °C ~ 40 °C
Temperatura de almacenamiento:	-40 °C ~ 60 °C
Humedad:	5 ~ 95% de humedad relativa, sin condensación
Descarga electrostática:	Confirme a +/- 15KV de descarga de aire y +/- 8KV de descarga de contacto
Especificaciones de caída:	Soporta múltiples caídas de 1.5m en concreto
Seguro:	
EMI / RFI:	FCC Clase A y CE
Seguridad con láser:	Producto láser CDRH clase 2

Detalles del producto:



*Handheld Laser
Barcode Scanner*

OCBS-L012

||| Product Picture





||| Features

Simple but not easy

Handheld laser barcode scanner



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined



with future-proofing;



Grey and Black Color available

All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive

2. By sea: around 2-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.





Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: [ocomsales01](https://www.skype.com/people/ocomsales01); MSN: ocomsales01@hotmail.com

Ali TM: [cn1001868228](https://www.aliexpress.com/item/cn1001868228); QQ: 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products

Documentos importantes:

¿Quieres saber más producto información? Por favor Haga clic aquí.

Especificación

Manual de usuario