

Υψηλής ποιότητας 433 MHz ή ενός κωδικού QR ασύρματο Bluetooth 2D ραβδοκώδικα με βάση

Μοντέλο: OCBS-W231-4/B

Χαρακτηριστικά γνωρίσματα:

- 1, 433 MHz ασύρματης επικοινωνίας εξ αποστάσεως 300 m εξωτερική, εσωτερική 100 m? Η απόσταση από το Bluetooth ασύρματη εξωτερική 20 m και 10 m σε εσωτερικό χώρο?
- 2, εξοπλισμένα με φόρτιση και επικοινωνία
- 3, ένα μαλακό πλαστικό κάλυμμα να προστατεύσει το φακό και ένα ανυσματικό σημαντικά βελτιώνει την απόδοση του αντι-σταγόνα?
- 4, γραμμικούς κώδικες στην οθόνη των υπολογιστών και κινητών τηλεφώνων μπορούν να σαρωθούν?
- 5, δεν χρειάζεστε τους οδηγούς, plug & play?
- 6, μπορεί να αποθηκεύσει περισσότερα από 10 000 κομμάτια των δεδομένων.
- 7, πολλαπλές σαρωτές μπορεί να συνδεθεί σε ένας δέκτης (433 MHz).

Παράμετροι:

Έχοντας μια πηγή φωτός	617 nm LED
Πηγή φωτός φωτισμού	625 nm LED
Σάρωση γωνία	39 ° (H) 25 ° (V)
Η γωνία της περιστροφής	0-360 °
Γωνίας ανύψωσης	65 °
Γωνία κλίσης	60 °
Αντίθεση εκτύπωσης	Υψηλότερο από 25%
1 d	UPC/EAN, UPC/EAN με supplementals, BooklandEAN, ISSN, κουπόνι UCC extended δωρεάν Code128, GS1-128, ISBT 128, κώδικας 39, κώδικας 39 πλήρη ASCII, Κωδικός 39 Trioptic, κώδικας 93, ο κώδικας 32, Code11, πίνακας 2 5, Interleaved 2 από 5, διακριτά 2τουπαρρητήματος 5, Codabar, MSI, 2, 5, Barvariants δεδομένων, GS1, 3 5, ISBT Concat Κορεατικά
2D	Τύπος PDF417, MicroPDF417, σύνθετα κώδικες, TLC-39, DataMatrix, Maxicode, QR code, των Αζτέκων, MicroQR
Διεπαφή	USB (καλώδιο ασύρματο δέκτη)
Εμβέλεια επικοινωνίας	433 MHz: μέσα: 100 m? Εξωτερικά: 300 m (μέγ.) Bluetooth: Εσωτερικό: 10 m Εξωτερικά: 20 m (μέγ.)
Θερμοκρασία λειτουργίας	-10 βαθμούς C - 45 βαθμούς C
Θερμοκρασία αποθήκευσης	-20 ° C - 65 ° C
Υγρασία λειτουργίας	5-85%
Περιεκτικότητα σε υγρασία κατά τη διάρκεια της αποθήκευσης	5% - 95%
Την ανθεκτικότητα της	Μπορεί να αντέξει μια ποικιλία από 1,5 m για σκυρόδεμα
Ισχύς εισόδου	5 v DC, 280mA

Χρόνος φόρτισης	6 h		
Μπαταρία	1500mAh		
Φωτεινότητας	Εσωτερικό: 3.000 LUX max? Ηλιακό φως: max 86000 LUX		
Βαθμός IP	Ip42		
ΑΠΟΚΩΔΙΚΟΠΟΙΗΣΗ ΣΕΙΡΕΣ			
Μια τυπική απόδοση *	Τυπικό εύρος λειτουργίας		
	Σειρά HD εστίασης		
Bar code τύπου	Η πυκνότητα των συμβόλων	Κοντά σε:	Πολύ
Ο κώδικας 39	5.0 μίλια	5 mm	90 mm
100% από το ΡΑΒΔΟΚΩΔΙΚΑΣ UPCA	13,0 μίλια	8 mm	200 mm
Ο κώδικας 39	20,0 μίλια	8 mm	250 mm
PDF 417	6,8 μίλια	5 mm	95 mm
Τα δεδομένα μήτρα	10.0 μίλια	5 mm	110 mm
QR code για	20,0 μίλια	10 mm	150 mm
Ανάλυση κώδικα 1 d 39	4 mil		
Το ψήφισμα του 2D μήτρα δεδομένων	10 mil		
Υλικό	ABS + PC		
Μια διάσταση	Σαρωτή (70 * 95 * 168 χιλ.) βάση (145 * 112 * 74 mm)		
Καθαρό βάρος	Βάση 185 g σαρωτή 186 γραμμάρια		
Πληροφορίες για την παραγγελία:	OCBS-W231-4: 2D barcode σαρωτή ασύρματος 433 MHz από την κούνια		
	OCBS-W231-B: 2D σαρωτή με barcode Bluetooth λίκνο		



433MHZ OR BLUETOOTH
WIRELESS 2D BARCODE SCANNER
WITH CRADLE

FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT
INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

ocominc.com

ocominc