

High Resolution Auto Cutter Cheap OCOM POS 80 Thermal Receipt POS Printer

(Model No.: OCPP-80G)

Features:

1. Desktop or wall-mounted type for option.
2. Supports multi 1D barcodes and 2D codes printing.
3. 100M Ethernet port, ultra high speed data transmission.
4. Supports 256KB NV Logo storage and 2M big buffer memory.
5. Supports black mark detection and order reminding function, compatible with OPOS driver.
6. Supports printing status monitor and anti-losing order function.

Technical parameters

| | |
|--------------------------|--|
| Printing method: | Direct thermal |
| Printing speed: | 230mm/s □260mm/s |
| Roll width: | 79.5±0.5mm |
| Print diameter: | Φ80mm |
| Paper thickness: | 0.06-0.08mm |
| Column capacity: | 576dots/line512 Dots/line |
| Line's pacing : | 3.75mm□Adjustable by commands□ |
| Print command: | Compatible with the ESC/POS command |
| Interface type: | Serial+USB+Lan/36P parallel port/25P serial +USB/LAN |
| Cutters life: | 1million cuts |
| Print head life: | 100 km |
| Input buffer : | 2048Kbytes |
| NV Flash: | 256Kbytes |
| Power adaptor: | AC110V/240V□50~60Hz |
| Power supply: | DC 24V/2.5A |
| Cash drawer supply: | DC 24V/1A |
| Work environment: | Temperature(0□45) humidity(10□80%)□Non- condense□ |
| Work environment: | Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense |
| Storage environment: | Temperature(-10□60°C); Humidity(10□90%) |
| Character size: | ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm |
| Barcode: | UPC-A/UPC-E/JA□EAN13□JAN8□EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options) |
| Characters: | PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863□Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□PC852 □Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□ |
| Physical characteristics | Weight: 1.25Kg; Appearance size: 190×145×143mm (length * width * height) |



OCPP-80G





OCPP-80G







OCPP-80G





OCP-80G





OCPP-80G



ocom
At your side

