

15.8 Inch Andorid/Windows All-In-One Self-service POS System

(M/N:POS-1508-W/A)

OCOM Wide-screen POS terminal has stylish and ultra slim body desgin,It has Android and windows OS motherboard for option,it is easy to install 2nd display,MSR or VFD as moudules by customers.This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices

Features:

- Intel Celeron series and Android board for option
- Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option
- Multi-point projected capacitive touch panel
- Optional side MSR and VFD220 customer display
- Ture flat and water-proof/scratch-resistant surface display

Specification

Model	POS-1508-W	POS-1508-A
Name	15.8 inch Windows touch screen pos terminal	15.8 inch Android touch screen pos terminal
Housing	ABS plastic and metal combined	
Color	Whole white color machine body usually	
Display		
Main screen size	15.8 inch touch screen monitor	
Resoluiton	1920*1080	
Brightness	350cd/m2	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.8 and 15.6 inch display W/o touch function, resolution1920*1080 resolution for option	
Performance		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4th generation CPU for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option	On board 2GB DDRIII,4GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB	16GB eMMC, support 32GB TF card expanded
Audio	On board Real Tek ALC662 audio chip ALC5640	On board Real Tek audio chip ALC5640
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option
Operating System	Windows7/8/10, Embedded,WEPOS,Linux	Android 8.1
Scanner	640*480 CMOS 1D/2D Barcode scanner	
Speaker	4 Ohm 3W speaker	
Printer	58/80 mm thermal printer with auto cutter	
Connectivity		
External I/O port(J1900 and RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB *5	
	N/A	TF card*1(SIM card*1 for option)
	RJ11 for Cash drawer *1	

Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508

