

**Scanner Pos codici a barre laser
(Modello: OCB-LA04)**

CARATTERISTICHE TECNICHE:

| | |
|------------------------------------|--|
| Performance Caratteristiche | |
| Luce Fonte: | Visibile laser (650-670nm) |
| Scansione Voto: | 100 scansioni al secondo |
| Lettura Distanza | 2.5 ~ 600 millimetri (100% UPC / EAN) |
| Scanner Tipo: | Bidirezionale |
| Risoluzione: | 0,10 millimetri (4mil) a PCS 0.9 |
| Stampa Contrasto minimo: | 20%, differenza minima riflettente (@ 650nm) |
| Decodificare Possibilità: | UPC / EAN, UPC / EAN con Supplementals, UCC / EAN128, il codice 39, codice 39 ASCII completa, codice 39 Trioptic, codice 128, codice 128 ASCII completa, Codabar, Interleaved 2 of 5, discreto 2 su 5, codice 93, MSI, codice 11, ATA, varianti RSS, cinese 2 di 5 ... |
| Fisico Caratteristiche | |
| Interfacce Supportato: | PS2, RS232, USB |
| Voltaggio: | DC + 5V +/- 5% |
| Corrente: | 100 mA |
| Inattivo Corrente: | & Lt; 40 mA |
| Potere Fonte: | Ospite potere o esterna (RS232) Alimentazione |
| Lettura Angolo | Inclinazione 45 ° di elevazione 60 ° |
| Dimensioni: | L165.42mm X W69.72mm X H89.67mm |
| Peso: | 140g (senza supporto) |
| Stare in piedi | Con |
| Colore: | Avorio e nero |
| Utente Ambiente | |
| Operativo Temperatura: | 0 °C ~ 50 °C |
| Immagazzinamento Temperatura: | -40 °C ~ 70 °C |
| Umidità: | 5 ~ 95% umidità relativa, senza condensa |
| Elettrostatica Scarico: | Conferma di +/- 15KV scarico dell'aria e +/- 8KV di scarica a contatto |
| Goccia Caratteristiche tecniche: | Resiste 1.5m multipla cadute su cemento |
| Sicuro: | |
| EMI / RFI: | FCC Classe A e CE |
| Laser di sicurezza: | CDRH Class 2 laser prodotto |

Scheda Prodotto:



*Handheld Laser
Barcode Scanner*

OCBS-LA04



Product Picture





Features

Simple but not easy

Auto-Induction built in,
green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported



CDurable construction combined with future-proofing



|| All-round show





Parameter

| Performance Characteristics | |
|-----------------------------|--|
| Light Source: | Visible laser (650-670nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) at PCS 0.9 |
| Print Contrast Minimum: | 20%, minimum reflective difference (@650nm) |
| Decode Capability: | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| Physical Characteristics | |
| Interface Supported: | PS2, RS232, USB |

| | |
|--------------------------|--|
| Interfaces supported: | RS232, RS485, USB |
| Voltage: | DC+5V+/-5% |
| Current: | 100 mA |
| Idle Current: | <40 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L165.42mm X W69.72mm X H89.67mm |
| Weight: | 140g (without stand) |
| Stand | With |
| Color: | Ivory and black |
| User Environment | |
| Operating Temperature: | 0°C~50°C |
| Storage Temperature: | -40°C~70°C |
| Humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| Safe: | |
| EMI/RFI: | FCC Class A and CE |
| Laser Safety: | CDRH class 2 laser product |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union

- 7. Escrow
- 8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.





I documenti rilevanti:

Vuoi saperne di più inf produttoormazione?Per Favore Clicca qui.

[Specificazione](#)
[Manuale utente](#)