

## 15-inch Touch POS terminal With Aluminum Base

(M/N:POS-8617Plus-B)

### Features:

- Intel Celeron J1900 Quad core 1.99 GHZ
- 4GB RAM and 64GB SSD (default)
- Higher configuration for optional
- Multi-point capacitive touch
- Rugged aluminum base and shell
- Modular design for easy assembly and disassembly
- The shell reserves a hard disk convenient insertion slot
- Pole display, secondary screen, MSR, fingerprint, RFID module for optional
- The secondary screen and customer display module support four-way angle adjustment



### Applications:

- ❖ Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- ❖ Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- ❖ Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- ❖ Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

### Parameter

Model	POS-8617Plus-B
Color	Black
Optional Peripherals	VFD220, LCD220 pole display, MSR, RFID, 10.1 inch secondary screen, fingerprint
Main Board	Intel Celeron Processor
CPU	Intel Celeron J1900 Quad core 1.9 GHZ
Chipset	Intel NM70
Memory Support	DDR III 1066/1333 * 1 4GB (default)
Hard Driver	SSD 64GB (default)

**Product specifications are subject to change without prior notice.**

**OCOM Technologies Limited**

**Address:** 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

**Website:** www.ocominc.com, www.possolution.com.cn;

**E-mail:** ocom@ocominc.com;

**Tel/Fax:** +86.755.8605.3207;



LCD panel Size	15.1inch TFT LCD
Brightness	350cd/m <sup>2</sup>
Resolution	1024*768(max)
Touch Screen	Multi-point capacitive touch

View Angle	Horizon: 150; Vertical :140
I/O port	1* power button 12V DC in jack*1
	HDMI*1
	VGA(15Pin D-sub)*1
	LAN:RJ-45*1
	USB(2.0)*4 and USB(3.0)*2
	RS232*2
	MIC IN and Audio out*1
	Operating temperature
Storage temperature	-20°C to 60°C
Compliance	FCC Class A/CE Mark/LVD/CCC
Operating System	Windows XP above, Embedded,WEPOS, Linux
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put

**Product specifications are subject to change without prior notice.**

**Together We Quest For The Best**