

Draagbaar Draadloze Barcode Scanner

(Model:OCBS-W700)

SPECIFICATIES:

| FYSIEKE characteristics | |
|-------------------------------------|---|
| Lichtbron: | Zichtbare rode laser 650 nm |
| Scanner Afmetingen: | 160mm * 70mm * 40mm(B * H * D) |
| Gewicht: | 300G |
| Materiaal: | ABS + PC |
| Scannen Mode: | Een lijn scannen; Handmatig / Automatisch |
| Indicator Way: | Zoemer en Indicator Light |
| PERFORMANCE characteristics | |
| Breedte van Scan Field: | 20mm @ scannervenster 260mm @ 260mm |
| Diepte van het Scan Field: | 4mil (0.1mm) / 5-60mm 5mil (0.12mm) / 10-100mm 10mil (0,25 mm) / 15-250mm 35mil (0,89 mm) / 140-600mm 43mil (1.1mm) / 150-800mm |
| Scansnelheid: | 120 scans / sec |
| Scan Precisie: | 0.10mm (pcs0.9) |
| Printing Contrast: | Minimaal 30% reflectie verschil |
| Error Rate: | 1 / (6 miljoen) |
| Decodeermogelijkheid: | Internationale algemene 1D barcodes |
| Huidige: | 60mA (werken); 5uA (standby) |
| Het scannen van Hoek: | 32 ° |
| Scannen Elevation: | 68 ° |
| Het scannen van Hoek van Avertence: | 52 ° |
| Werken Frequentie: | 2.4GHz |
| Communicatie Afstand: | 100m (Open Places) 20m (binnen) |
| Communicatie Interface: | USB |
| Gebruikersomgeving characteristics | |
| Drop Specificatie: | 2m vrije val |
| Niveau van de Laser: | Niveau-1 laser veiligheidsnorm |
| Laad Vermogen: | DC5V |

Product Details:



Wireless Barcode Scanner

OCPP-W700

Product Picture





Features

Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);



Outside communication distance can



reach 100m, inside is 20m;;

20 scanners can work in the same field without interfering each other;



Plug and play;



800mA big capacity Li-battery.



||| All-round show





Parameter

| PHYSICAL CHARACTERISTICS | |
|-------------------------------|---|
| Light Source | Visible Red Laser 650 nm |
| Scanner Dimensions(W * H * D) | 160mm * 70mm * 40mm |
| Weight | 300G |
| Material | ABS + PC |
| Scanning Mode | One line scanning; Manual / Automatic |
| Indicator Way | Buzzer and Indicator Light |
| PERFORMANCE CHARACTERISTICS | |
| Width of Scan Field | 20mm@scanner window 260mm@260mm |
| Depth of Scan Field | 4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm |

| | |
|---|-------------------------------------|
| Scan Speed | 120 scans/sec |
| Scan Precision | 0.10mm (pcs0.9) |
| Printing Contrast | Minimum 30% reflection difference |
| Error Rate | 1/(6million) |
| Decode Capability | International general 1D barcodes |
| Current | 60mA (working); \leq 5uA(standby) |
| Scanning Corner | 32° |
| Scanning Elevation | 68° |
| Scanning Angle of Avertence | 52° |
| Working Frequency | 2.4GHz |
| Communication Distance | 100m (Open Places) 20m (Indoor) |
| Communication Interface | USB |
| USER ENVIRONMENT CHARACTERISTICS | |
| Drop Specification | 2m free fall |
| Laser Level | Level-1 laser safety standard |
| Charge Power | 5VDC |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



© 2012-2013 All rights reserved. www.cominc.com



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



Relevante documenten:

Wilt u meer product inf wetenormatie?Alstublieft Klik hier.

[Specificatie](#)