

High Quality 433 MHz of Bluetooth Wireless QR Code 2D Barcode Scanner Met Cradle

Model: OCBS-W231-4 / B

Kenmerken:

- 1, 433Mhz draadloze communicatie op afstand outdoor 300m, 100m indoor; Bluetooth draadloze communicatie op afstand outdoor 20m en 10m indoor;
- 2, uitgerust met communicatie en oplaadstation
- 3, Soft plastic te dekken om de lens te beschermen en te schetsen sterk verbetert de anti-drop prestaties;
- 4, kan het scherm van de streepjescode op computers en mobiele telefoons 'worden gescand;
- 5, Geen behoefte bestuurder, plug and play;
- 6, kan meer dan 10.000 stuks gegevens op te slaan;
- 7, kunnen meerdere scanners worden aangesloten op een ontvanger (433MHz).

parameters:

| | | | |
|--------------------------|--|---------------------|-----|
| Het streven Lichtbron | 617 nm LED | | |
| Verlichting Lichtbron | 625 nm LED | | |
| scanning Hoek | 39 ° (H) x 25 ° (V) | | |
| Draaihoek | 0-360 ° | | |
| Elevation Angle | ± 65 ° | | |
| Hellingsgraad | ± 60 ° | | |
| Print Contrast | Hoger dan 25% | | |
| 1D | UPC / EAN, UPC / EAN met supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Volledige ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 van 5, Interleaved 2 of 5, Discrete 2 van 5, Codabar, MSI, de Chinese 2 van 5, GS1 gegevens Barvariants, Koreaans 3 van 5, ISBT Concat | | |
| 2D | PDF417, MicroPDF417, Composiet Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec | | |
| Interface | USB (wireless ontvanger kabel) | | |
| communicatie afstand | 433mhz: Inside: 100m; Buiten: 300m (Max) Bluetooth: Binnen: 10m; Buiten: 20m (Max) | | |
| Temperatuur | -10 ° C - 45 ° C | | |
| Bewaar temperatuur | -20 ° C - 65 ° C | | |
| luchtvochtigheid regelen | 5% -85% | | |
| Opslagvochtigheid | 5% -95% | | |
| Duurzaamheid | Bestand tegen meerdere 1.5m druppels op beton | | |
| Macht van de input | DC 5V, 280mA | | |
| Laadtijd | 6h | | |
| Accu | 1500mAh | | |
| Lumination | Binnen: 3.000 LUX max; Buiten zonlicht: 86000LUX max | | |
| IP-Grade | IP42 | | |
| DECODE BEREIKEN | | | |
| Typische Prestaties * | | Typische werkbereik | |
| | | HD Focus Range | |
| Bar Code Type | symbool Density | In de buurt | Ver |

| | | | |
|----------------------------|--|------|-------|
| code 39 | 5,0 mil | 5mm | 90mm |
| 100% UPCA | 13,0 mil | 8mm | 200mm |
| code 39 | 20,0 mil | 8mm | 250mm |
| PDF 417 | 6.8 mil | 5mm | 95mm |
| data Matrix | 10,0 mil | 5mm | 110mm |
| QR code | 20,0 mil | 10mm | 150mm |
| Resolutie 1D Code 39 | 4 mil | | |
| Resolutie 2D Data Matrix | 10 mil | | |
| Materiaal | ABS + PC | | |
| Dimensie | Scanner (70 * 95 * 168mm) Base (145 * 112 * 74mm) | | |
| Netto gewicht | Scanner 185g Base 186g | | |
| Informatie ordenen: | OCBS-W231-4: 433MHz draadloze 2D barcode scanner met houder | | |
| | OCBS-W231-B: bluetooth 2d barocde scanner met houder | | |



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



**PRODUCT
INORMATION**

| | |
|------------------------|--|
| Aiming Light Source | 617 nm LED |
| Lighting Light Source | 625 nm LED |
| Scanning Angle | 39° (H) x 25° (V) |
| Rotation Angle | 0 - 360° |
| Elevation Angle | ± 65° |
| Tilt Angle | ± 60° |
| Print Contrast | Higher than 25% |
| 1D | UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat |
| 2D | PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec |
| Interface | USB (Wireless receiver cable) |
| Communication distance | 433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max) |
| Operating Temperature | -10 deg C - 45 deg C |
| Storage Temperature | -20 deg C - 65 deg C |
| Operating Humidity | 5%-85% |
| Storage Humidity | 5%-95% |
| Durability | Withstands multiple 1.5m drops to concrete |
| Input Power | DC 5V, 280mA |
| Charging time | 6h |
| Battery | 1500mAh |
| Lumination | Inside: 3.000 LUX max; Outside sunlight: 86000LUX max |
| IP Grade | IP42 |

| DECODE RANGES | | | |
|---------------------------|---|------------------------|-------|
| Typical Performance* | | Typical Working Ranges | |
| | | HD Focus Range | |
| Bar Code Type | Symbol Density | Near | Far |
| Code 39 | 5.0 mil | 5mm | 90mm |
| 100% UPCA | 13.0 mil | 8mm | 200mm |
| Code 39 | 20.0 mil | 8mm | 250mm |
| PDF 417 | 6.8 mil | 5mm | 95mm |
| Data Matrix | 10.0 mil | 5mm | 110mm |
| QR Code | 20.0 mil | 10mm | 150mm |
| Resolution 1D Code 39 | 4 mil | | |
| Resolution 2D Data Matrix | 10 mil | | |
| Material | ABS+PC | | |
| Dimension | Scanner (70*95*168mm) Base (145*112*74mm) | | |
| Net Weight | Scanner 185g Base 186g | | |
| Ordering Info. | 433MHz wireless communication (OCBS-W231-4) | | |
| | Bluetooth communication (OCBS-W231-B) | | |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

