2016 restaurant 15 inch all in one pos touch terminal (M/N:POS8829)

Feature:

- 1.Good-looking design is suitable for many POS field
- 2.Low power-consumption solution guarantees its stable quality and safety
- 3.LED/LCD customer display optional
- 4.MSR optional
- 5.Wifi optional

Application:

- 1.Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 2.Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- 3. Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- 4. Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Specifications:

| pecifications. | |
|---------------------------|---|
| Model | POS8829 |
| Optional Color | Black/ Wine red |
| Optional Peripherals | ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI |
| Main Board | Intel Chipset |
| CPU | 1037U dual core 1.8G |
| Chipset | 1037U + ICH8 Chipset |
| Memory Support | DDRIII 1066/1333*1 2GB(up to 4GB) |
| Hard Driver | SSD32GB |
| LCD panel Size | 15 inch TFT LCD |
| Brightness | 350cd/m |
| Resolution | 1024*768(max) |
| Touch Screen | 5 wire resistive touch screen |
| View Angle | Horizon: 150; Vertical: 140 |
| I/O port | 1* power button |
| | PS2 mouse*1; PS2 keyboard*1 |
| | Serial*3 DB9 male |
| | Parallel * 1, DB25 Parallel port |
| | VGA(15Pin D-sub)*1 |
| | LAN: RJ-45*1 HDMI * 1 |
| | USB(2.0) * 6 |
| | Audio out*12*Internal Speaker(option), MIC IN*1 |
| Operating temperature | 0 to 40 degree centigrade |
| Storage temperature | -20 to 60 degree centigrade |
| Power Consumption | 35W(max) |
| Compliance | FCC Class A/CE Mark/LVD/CCC |
| Packing dimension/ Weight | 440*270*425mm / 8 KGS |
| Operating System | Windows XP Professional Embedded (WEPOS, Linux compatible) |
| Power adapter | 110-240V/50-60HZ AC power Input, DC12/5A output |