

4inchesBluetooth Label Thermal Printer

(M/N:OCBP-M1001)

Feature:

- 1.Canprint Label sticker and Receipt Paper
- 2.Easyto set the print density and Langue
- 3.Multi-interfaceand different paper size support
- 4.LCD display can show the printerparameter settings
- 5 Canquickly print imge barcodes and forms.
- 6.MultipleSensor Supported Black mark,Label interval
and Paper end detection

Printing Method	Thermal Line
Printing Speed	80mm/s (Thermal Paper)
	70mm/s (Label Sticker)
Resolution	8 dots/mm
Effective Printing Width	100mm/72mm/48mm/37.5mm
Character Set	ASCII, GB18030 (Chinese), BIG5, Codepage
Print Font	Font A: 12*24; Font B: 8*16
Self-defined Character	Yes
Paper Type	Thermal paper/Label Paper
Paper Roll Diameter	40mm(max.)
Roll Core Inner Diameter	13mm(min.)
Paper Thickness	0.06~0.16mm
Paper Supply Method	Drop-in easy paper loading
TPH	50km
Barcode	1D: EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25
	2D: PDF417,QRCODE,DATA Matrix
Emulation	CPCL/ESC-POS
Driver	Windows 98 / ME / 2000 / NT / XP / 2003 Server/Vista/Win7/Win 8/Win10
Sensor	Paper End Sensor,Black Mark, Label Interval
Interface	USB/Bluetooth
Button	Power, Feed, Mode
Indicator	Power, Feed, Mode
Memory	Flash: 512kb; RAM: 128kb
Receive Buffer Size	32K
SDK	Windows CE; Windows Mobile 5.0/6.0; Symbian; Blackberry and Android
Multi-languages	46 codepages
Power Supply (Adapter)	DC9V/2A
Battery Power	7.4V, 2300mAg rechargeable Li-ion battery
Battery Charge	100m continuous printing
Charge Time	less than 3 hours
Battery Duration	360 hours
Gross Weight	500g (Including battery)

Printer Dimension(WxLxH)	140mm x115mm x 51mm
Color	Black
Operating Temp	-10-50°C
Operating Humidity	10%-80%
Application	Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Supermarket
Accessories	Battery,Charger USB Cable,CD Driver,Leather Case and Paper-roll Option: vehicle charger



OCBP-M1001



www.ocominc.com

