58mm thermal receipt printer OCPP-587-R RS232/COM/Serial Port

(M/N:OCPP-587-R)

Product description:

OCPP-587 is a Mini 58MM thermal printer, the design exquisite fashion, small and smart,
with highly technological sense. Using large motor and a big gear movement design, drag 83MM large diameter roll and ach ieve 130 mm / s high speed printing at the same time, the perfect solution to solve the problem of common 58mm printer s upport small diameter roll, print speed slow ,enable print more efficient. At the same time, provides a rich interface ,includin g network port (100M), WIFI, Bluetooth, GPRS, enable print more flexible and convenient.

Product performance:

●Appearance compact design, fashion technology;
●Easy paper feed structure, simple and convenient operation;
●High reliability of large motor and large gear movement;
●130 mm / s speed print, significantly improve the printing efficiency;
●Big paper warehouse design, the perfect support for 83MM large diameter rolls;
●Rich interface optional: USB, COM, Internet (100M), WIFI, Bluetooth, GPRS;
●Support GB18030 large font and multi language ;
●Supports LOGO and graphics downloads and print;
●Supports Windows, Linux, Android and IOS system print;
●100M Ethernet interface, print quickly while avoiding losing bills.

Printer Parameters:

Items		Parameters
	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line（8dots/mm（203dpi）
	Printing Speed	130mm/Second
	Interface Type	USB、COM、Internet（100M）、WIFI、GPRS、Bluetooth
Print parameters	Line Spacing	3.75 mm（Can adjust line spacing by command）
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter（Font A/（1.5×3.0mm（12×24/（ Font B（1.1×2.1mm（9×17/、Simplified/Traditional Chinese（3.0×3.0mm(24×24 Dots）
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code（UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D bar code（QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤83mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input（AC 100V-240V,50-60Hz Outout（DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	750g
	Dimension	180*115*127(MM)
Environment	Working	Temp（5 ~ 45℃） Humidity（10 ~ 80%
	Storage	Temp（-10 ~ 50℃ ）Humidity（10 ~ 90%（No dew（
Reliability parameter	Print Head Life	100KM（print density≤12.5）
Software	Driver	Android,IOS,Linux,,WinXP,Win7,Win8,Win8.1,Win10

Aocom®
At your side

OCPP-587

Thans & Best Regard
Harold Hu

****

OCOM Technologies Limited
Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;
Website: www.ocominc.com, www.possolution.com.cn ;
E-mail: sales14@ocominc.com ;
Skype:sales14@ocominc.com
MSN: ocomsales14@hotmail.com ;
Whatsapp: 0086.18948789890;
Wechat: 0086.18948789890;
Mobile: 0086.18948789890;

QQ: 1467261417;
Tel: 0086.755.86053207-814;
Fax: 0086.755.86053207-868;