

## Andorid USB nos thermal receipt printer (Model: OCPP-586)

### Specification:

pos printer,thermal printer,thermal receipt printer,thermal pos printer

Printing Method	Direct thermal
Print Density	384dots/line (203DPI)
Character Size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JAN13□EAN13□JAN8□EAN8□CODE39 QRCODE (Optional function)
Printing Command	Compatible with EPSON ESC/POS
Language	OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/ Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/OEM852/ OEM858/IranII/Latvian/ Arabic/PT151,1251/OEM747/WPC1257/Vietnam/OEM864/Hebrew/WPC1255/Thai
Printing Speed	90mm/sec
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
MCBF(life)	50km
Dimension	190*132*119mm
Gross Weight	1.2KG
Auto Cutter	manual cutter
Sensor	Paper Near End Sensor, Paper End Sensor, Cover open sensor
Roll Paper	Φ75mm
Interface	RS-232C, Parallel, USB, LAN
Driver	Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 Win8 Win10 compatible with ESPON
Printer Supply	DC12V/3A
Cash Drawer Control	DC12V/1A
Working Temperature	0-45°C, Humidity: 10-80%
Saving Temperature	-10-60°C, Humidity: 10-90%

### Product Details:



### Relevant documents:

\*Specification

\*Program Manual

\*Instruction Manual

\*Driver for WinXP Win2000 WinVista Win7 Win8-32bit

\*Driver for Win7and Win8-64bit

\*Driver for Linux

\*Printer Parameters Setting Tools

\*USB Printdemo(Application Software demo)

\*SDK for Android

\*CD Files