### **BT-100U Pos Cash Drawer USB Trigger**

## Feature:

- 1. Cash drawer can be directly connected to the computer with BT-100U;
- 2. Powered by USB bus, external power is not required;
- 3. Allows for "Hot Plugging", plug and play connectivity;
- 4. No need to set the COM property;
- 5. Suitable to any cash drawer command. Write any data to COM port will open the cash drawer.

# **Specification:**

BT-100U cash drawer trigger is designed to provide USB interfacing to the cash drawer. This allows the cash drawer, which is previously connected to POS printer or cash register, to be directly connected to a USB port of the computer. This means through the USB Trigger the cash drawer can be directly connected to the computer when this no printer used in the POS system.

The BT-100U USB trigger module uses a virtual serial port driver, making it appear to software like a standard RS232 serial port. This way existing POS software can communicate with the USB cash drawer trigger as though connected to a serial port. A unique serial number is assigned to each USB trigger module and driver software will assign the next available serial port to each device it recognizes(multiple triggers can be used on one computer).

### **Application Area:**

1 small city card spending and recharge system

Two campus card system area

- 3 members, counter consumer credit management system
- 4.RFID electronic label applications
- 5 hotels, restaurants, entertainment
- 6. Tobacco industry
- 7. Telecommunications Industry
- 8 health insurance industry
- 9 Clothing, Business

#### **Pictures:**





Contact: Harold Hu

OCOM Technologies Limited

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: sales14@ocominc.com; Skype:sales14@ocominc.com MSN: ocomsales14@hotmail.com;

Whatsapp: 86.18948789890;

Wechat: 18948789890(ocomsales14);

Mobile: 86.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814; Fax: 0086.755.86053207-868.