

Barcode Label Printer Supports Bartender  
(Model No.: OCBP-003)

Features:

- | Two printing methods available: Thermal Transfer with ribbon and Direct Thermal;
- | Label paper auto position;
- | Labels peel off, tear off automatically;
- | Compatible with plenty of label software;
- | BMP, PCX images download store;
- | Parallel , USB ,Serial and Power port available;
- | Support PDF417, QR CODE, DOTMATRIX;
- | Suit for thermal paper rolls or self-adhesive labels;

Specifications:

Printer Model	OCBP-003
Resolution	300 DPI (12dots/mm)
Printing Method	Direct Thermal / Thermal Transfer
CPU	32 BIT
Sensor	Type: Label gap Detection: label length auto sensing or program command setting
Printing Speed	2~5inch / Sec
Max Printing Length	1651 mm
Max Printing Width	81mm(3.18")
Media	Paper Roll External Diameter: Maximum Diameter 127mm Paper Roll Axis: 26 mm Paper Width: 20mm(0.78") ~ 90mm(3.54") Paper Thickness: 0.06mm(2.36 mil) ~ 0.254mm(10 mil) Media Type: Label gap, Continuous, folded
Ribbon	Types: Outward Roll External Diameter: 67mm (Max) Length 300M Width: 30 mm ~ 90 mm Core Inner Diameter: 25.4mm (1inch) Material: outward rolling
Interface	Parallel Port+ USB+ Serial
Transmission Setting	Baud Rate 9600, XON/XOFF, RTS/CTS
Control panel	LED*2: Ready, Status Function Key*1: Feed
Power	AC 18V, 4000mA
Environment	Operating Temperature:5~45 Degree C Humidity 25-85% Storage Temperature: -10~50 Degree C Humidity 10~90%
Physical Dimension	Size: 186(W)×180(H)×290(D) Weight: 2.4KG (net)