

<b>Model</b>	OCBP-402DT
<b>Material</b>	Plastic housing
<b>Interface</b>	USB,USB+Bluetooth,USB+Bluetooth +WIFI, USB+LAN
<b>Processor</b>	32 bit CPU
<b>Memory</b>	4MB Flash Memory,320KB RAM
<b>Printer Head life</b>	50Km
<b>Power supply</b>	Input□AC 100V-240V,50-60Hz,Output□DC 24V/2.5A
<b>Accessories</b>	Power adapter,Power cable,USB cable,Manual, outside bracket for option
<b>Sensors</b>	Label edge detection, Out of paper detection, Gap detection, Black mark detection,Cover-open detection
<b>Gap height</b>	2mm Min
<b>Black-mark height</b>	2mm Min
<b>Font and bar-code rotation</b>	0°,90°,180°,270°
<b>Compatible command</b>	TSPL
<b>Printing</b>	
<b>Printing method</b>	Direct Thermal
<b>Resolution</b>	203 DPI
<b>Printing speed</b>	152mm /s Max
<b>Printing width</b>	30-108mm
<b>Printing length</b>	10-250mm
<b>Barcode</b>	
<b>Bar-code</b>	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Coda bar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code:PDF417, Maxi code, Data Matrix, QR code
<b>Font</b>	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
<b>Media</b>	
<b>Paper type</b>	Folded paper or roll paper, die-cut label, black mark paper
<b>Paper width</b>	30-118mm
<b>Media thickness</b>	0.06 ~ 0.22mm
<b>Physical</b>	
<b>Dimension</b>	220*112*102mm
<b>Weight</b>	Net: 1.02kg
<b>Package box</b>	248*140*170mm/1.87Kg
<b>8 in 1 carton</b>	516*300*360mm /12.4kg
<b>Environment</b>	
<b>Working temperature&amp; humidity</b>	0 to 45 degrees centigrade, 10%~80% No condensation
<b>Storage temperature&amp; humidity</b>	-20 to 60 degrees centigrade , 10%~90% No condensation