China POS thermal printer factory

Loading paper easy, waterproof, oil proof, dustproof; 260mm/sec high speed printing with automatic cutter, best printing quality and reliable performance; Support print prompt and error alarm; Support black mark sensor, reprint function; Compatible with EPSON ESC/POS; Support 128K bytes NV logo download store and print; Support printer status monitor function, control printer's status at any time; Support cash drawer driving;

80mm High Speed With Auto-cutter Pos Thermal Receipt Printer (Model: OCPP-804)

Specification:

Specification:	
Printing method	Direct thermal
Character size	ANK,FontA:12*24dots,FontB:9*17dots
Column capacity:	576dots/line OR 512dots/line
	PC347(Standard Europe), Katakana,PC850(Multilingual), PC860(Portuguese), PC863(Canadian-
Character set	French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252,
	PC866(Cyrillic#2), PC852(Latin2), PC858, IranII, Latvian, Arabic, PT151(1251)
Barcode	JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code
Printing speed	260mm/sec
Receive buffer	64k bytes
NV Flash	128k bytes
Paper width	79.5±0.5mm
MCBF(life)	100km
Printing command	Compatible with ESC/POS
Cash drawer control	DC 12-24V/1A
Paper thickness	0.06-0.08mm
Cutter	Auto Cutter
Roll paper	79.5±0.5mm* φ83mm
Interface	Serial/parallel/ USB
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7/Linux
Power supply	DC24V/2.5A
Power adapter input	AC 110V/220V, 50~60Hz; Output: DC 24V/2.5A
Dimension	200x145x137mm
Net Weight	1.56kg

Product Details:

x x x x x x x x x x x

Relevant documents:

Do you want to know more product information?Please Click here.

Specification User's Manual Printer Driver