China made low cost Handheld Laser Barcode Scanner-OCBS-L013

1) Handheld laser barcode scanner
2) High scan rate (100 scans/sec) and 10-520mm distance;
3) Excellent decode capability;
4) KBW, RS232 and USB supported;
5) Durable construction combined with future-proofing;
6) Grey yellow and Black Color available

## High Scanning Speed Handheld Laser Bar code Reader
### （Model No.: OCBS-L013)

## Specification:

| Performance Characteristics | |
|---|---|
| Light Source: | Visible laser (650nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance | 10 ~520mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) |
| Print Contrast Minimum: | 30%, minimum reflective difference (@650nm) |
| Error Rate: | 1/3000000 |
| Decode Capability: | UPC-A, UPC-E, Industrial 2 of 5, Interleaved 2 of 5, EAN8, EAN 13, Code 128, EAN 128, Code39, Code 93, Codabar 125, MSI/Plessey etc. |
| Physical Characteristics | |
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | 5V |
| Current: | 120 mA |
| Idle Current: | <30 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L175mm X W70mm X H100mm |
| Weight: | 150g (without stand) |
| Stand | Optional |
| Color: | Grey, black and yellow |
| User Environment | |
| Operating Temperature: | -20 - 45 degree centigrade |
| Storage Temperature: | -20 - 45 degree centigrade |
| Humidity: | 5~85% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| Safe: | |
| EMI/RFI: | Compliant with EN50081.parl standard |
| Laser Safety: | IEC 60825-1 Standard class 2 for laser products |