

# China pos system dual screen poswith MSR

(M/N:POS-8618)

## Features:

pos systemdual screen, touch screen pos terminal, pos touch screen

Intel Celeron 1037U dual core 1.8GHZ

HardDriverSSD32GB (default),SSD 64GB and HDD320G for optional

5 wireresistive touch screen(default),Capacitive screen for optional

Cardreader and VFD customer display for optional

I/OInterface Panel is hidden

## Applications:

pos systemdual screen, touch screen pos terminal, pos touch screen

Catering:hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer:Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation:sauna, spa, night club, theme park, casino and point of sales for lotteryticket

Commercial:information management terminals for parking lot, inn, aviation, subway,station and wharf

## Pictureshow:

pos systemdual screen, touch screen pos terminal, pos touch screen

✘		✘	
✘		✘	

## Parameter:

pos systemdual screen, touch screen pos terminal, pos touch screen

Model	POS8618
Optional Color	Black or White
Optional Peripherals	VFD220E
Main Board	Intel Celeron Processor
CPU	Intel Celeron 1037U dual core 1.8GHZ
Chipset	Intel NM70

Memory Support	DDRIII 1066/1333*1 2GB (default)
Hard Driver	SSD32GB (default)
LCD panel Size	15 inch TFT LCD
Brightness	350cd/m2
Resolution	1024*768(max)
Touch Screen	5 wire resistive touch screen
View Angle	Horizon: 150; Vertical :140
I/O port	1* power button 12V DC in jack*1
	PS2KB/MS*1
	Serial*1 DB9 male
	Parallel:1*DB25 Parallel port
	VGA(15Pin D-sub)*1
	LAN:RJ-45*1
	USB(2.0)*6
	Audio out*1 MIC IN*1
Operating temperature	0°C to 40°C
Storage temperature	-20°C to 60°C
Compliance	FCC Class A/CE Mark/LVD/CCC
Packing dimension/ Weight	410*310*410mm / 7.6 KGS
Operating System	Windows XP above, Embedded, WEPOS, Linux
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put

## Product Details:

possystem dual screen, touchscreen pos terminal, pos touchscreen

