Hanheld Wireless 1D Barcode Scanner (Model: OCBS-W600)

SPECIFICATION:

PHYSICAL CHARACTERSTICS Light Source: Visible Laser Diode (VLD) @ 650 nm-670nm Scanner Dimensions: 164mm * 67mm * 95mm(W * H * D) Receiver Dimensions: 130mm*45mm*129mm(W * H * D)	
Scanner Dimensions: 164mm * 67mm * 95mm(W * H * D) Receiver Dimensions: 130mm*45mm*129mm(W * H * D)	
Receiver Dimensions: 130mm*45mm*129mm(W * H * D)	
Material: ABS+TPR /Aluminium alloy	
Weight: 235g	
Scanning Mode: Hand-held; bidirectional Scanning Mode.	
Indicator Light: LED Red and Blue	
Buzzer: Buzzer Volume Adjustable	
PERFORMANCE CHARACTERSTICS	
60mm@30mm[From engine face]	
98mm@100mm[from engine face]	
Depth of Scan Field: 2.5-600mm[Contrast 0.9 Density 0.25]	
Scan Speed: 100 scans/sec	
Scan Precision: 0.10mm[4mil] PCS0.9	
Bit Error Rate: 1/(5million)	
UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39	
Decode Capability: ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codab	
Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variar	its,
Chinese 2 of 5	
Battery: 3.7V/750mAh,Li-ion	
Charge Time: 3.0 Hours	
Scan Time: 30 Hours	
Current: 100mA (working); 40mA(standby)	
Angles:Pitch:60°; Tilt: 45°	
Communication Distance: 30m	
Working Frequency: 2.4G	
Communication Interface: USB	
USER ENVIRONMENT CHARACTERSTICS	
Temperature: 0degree C to 50degree C (Operating), -40degree C to 70 degree C (Storage)	e)
Relative Humidity: 5%-90%(Non-Condensing)	
Drop Specification: Withstands repeated 1.5m drops to concrete surface	
Ambient Illumination:0~100,000 LUX	
Electrostatic Discharge: Conforms to ±12KV air discharge and ±6KV of contact discharge	
Safety Certificate: CE, FCC, Class 2, RoHS	

Product Details:

x x x x x x x x

Relevant documents:

Do you want to know more product information?Please Click here.

Specification