

# High Reading Performance on Curved Surfaces 1D Barcode Scanner and can Work with Excel (Model: OCBS-LA09)

## Specification:

|                             |  |
|-----------------------------|--|
| Performance Characteristics |  |
| Light Source:               | 650nm visible  |
| Scan Rate:                  | 200 scans per second   |
| CPU                         | 32 bit   |
| Reading Distance            | 2.5 ~600mm (100% UPC/EAN)  |
| Width of Scan               | 50mm@60mm, 220mm@200mm   |
| Scanner Type:               | Bi-directional   |
| Operation mode              | Auto Sense   |
| Resolution:                 | 3mil high resolution series / 5mil long depth field series   |
| Print Contrast Minimum:     | 30%, minimum reflective difference   |
| Decode Capability:          | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)series |
| Scanning Angle              | ±65°(tilt); ±60°(pitch); ±42°(yaw)   |
| Physical Characteristics    |  |
| Interfaces Supported:       | PS2, RS232, USB for option   |
| Voltage:                    | 5V DC±5%   |
| Current:                    | 85 mA (Operating); 100 (Max)   |
| Indicator                   | Beeper, LED  |
| Material                    | ABS+PC   |
| Stand                       | With   |
| Dimensions:                 | 156*68*83 mm (L*W*H)   |
| Weight:                     | 235g   |
| Color:                      | Grey or black  |
| User Environment            |  |
| Operating Temperature:      | 0°C~45°C   |
| Storage Temperature:        | -40°C~60°C   |
| Humidity:                   | 5%-90% (non-condensing)  |
| Electrostatic Discharge:    | Conforms to +/-15KV air discharge and +/-8KV of contact discharge  |
| Ambient Illumination        | 0 ~ 100,000 LUX  |
| Drop Specifications:        | Withstands multiple 1.5m drops to concrete surface   |
| Laser classification        | EN60825-1, Class 1   |

## Product Details:

