Black Mobile Adhesive POS Thermal Receipt Barcode Label Printer

Printing Method	Thermal Line
Printing Speed	80mm/s (Thermal Paper)
	70mm/s (Label Sticker)
Resolution	8 dots/mm
Effective Printing Width	100mm/72mm/48mm/37.5mm
Character Set	ASCII, GB18030 (Chinese), BIG5, Codepage
Print Font	Font A: 12*24; Font B: 8*16
Self-defined Character	Yes
Paper Type	Thermal paper/Label Paper
Paper Roll Diameter	40mm (max.)
Roll Core Inner Diameter	13mm(min.)
Paper Thickness	0.06~0.16mm
Paper Supply Method	Drop-in easy paper loading
TPH	50km
Barcode	1D: EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25
	2D: PDF417、QRCODE、DATA Matrix
Emulation	CPCL/ESC-POS
Driver	Windows 98 / ME / 2000 / NT / XP / 2003 Server/Vista/Win7/Win 8/Win10
Sensor	Paper End Sensor, Black Mark, Label Interval
Interface	USB/Bluetooth
Button	Power, Feed, Mode
Indicator	Power, Feed, Mode