OCPP-80F-UBW USB+Bluetooth+WIFI Ports 300mm/s Hight Speed Thermal Receipt Printer(M/N:OCPP-80F)

Features:

- 1.300mm/s printinghigh-speed, improve the printing efficiency
- 2.2048K super input buffer, to avoid losing bills
- 3. Support 1D,2D bar code printing
- 4. Support black mark orientation and re-print
- 5. Support printer monitoring function, to avoid losing bills;
- 6. Excellent waterproof, anti oil, anti-dust structure design
- 7.Movable baffle design, support 80MM, 58MM different width of paper roll printing.

Printer Parameters:

Item	Parameters		
Printing Method	Thermal Line		
Printing width	72mm		
	576 Dots/Line or 512 Dots/Line[8dots/mm,203dpi]	I	
Print speed	300mm/Second		
Interface	Internet[100M[]+USB+COM;USB+COM		
Line Spacing	3.75mm()Can adjust line spacing by command()	I	
Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 lines		
Character	standard GB18030 simplified / traditional Chinese Fonts	I	
Character Size	ANK character, Font A:1.5x3.0mm[]12x24 dots[]		
	FontB:1.1x2.1mm[9x17 dots[Simplified/Traditional Chinese:3.0x3.0mm(24x24 dots[]		
Extended character set	PC43/MatakanupC850PC860PC883PC865WestEurope/GreekHebrewEastEurope/iran/WPC1252PC866PC852PC858/iranii(Latvian/Wrabic/PT151.1251)PC737WPC/1257/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(Vetnam)i/ThaVletnampC864PC1001/(Latvian)i/PC1001/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257/HPC864I/(PT151.1251)WPC1257	Bar code	1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
	Supports bitmap download and print		2D barcode[QRCODE
Graphics printing			
	Half cut	l	
Type	Thermal		
Width	79.5±0.5mm		
Diameter	≤80mm		
	Easy feed(Clameshell feed)	l	
	ESCPOS		
	Input:AC 110V/220V,50~60Hz		
	Output-DC 24V/2.5A		
	DC 24V/IA	l .	
Input Buffer	2048K bytes		
NV Flash	256K bytes	I	
Weight	1.2KG		
Dimension	186*145*135	I	
Working	Temp:5~45 Centigrade,Humidity:10~80%	I	
Storage	Temp:-10 ~ 50 Centigrade, Humidity:10~90% (Nodew)	i	
Print Head Life	100KM(print density LE.12.5)	i	
Cutter Life	1000,000times		
Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1	I	

Products Review:





FAQ:

1. Warranty

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers'satisfication, our warranty of the products is about 12 months from the shipment normally, some designated models can have as long as 24 months warranty. For mass order, we can supply you some spare parts for local repair. And after that, you can returned failure parts for reworks.

2. Payment Terms

For mass order, you can pay us by using T/T, LC, Western Union, Escrow or others. About samples order, T/T, Western Union, Escrow, Paypal are acceptable. Escrow Service is powered by Alipay.com. Currently, you can pay using Moneybookers, Visa, MasterCard and bank transfer. You can also pay with select debit cards including Maestro, Solo, Carte Bleue, PostePay, CartaSi, 4B and Euro6000.

3. Shipment

We accept all kinds of shipping ways including: express, air, sea, car, or pick up by customers personally.

4. Sample Availability & Policy

After customers confirmed our specification, we are very glad to provide samples for testing and qualification. All samples should be paid before shippment, and the samples price is a little higher than mass order. When the mass order placed, we can return you the samples cost, or send you more products with the shippments. You can buy the samples from us directly using t/t, western uion, or paypal. And you online can also buy it o n our store a t aliexpress: http://www.aliexpress.com/store/403448?tracelog=minisite_CI The sample order is needed before we release to our factorie

5. After-sales Service:

* We have the top 1% level trade assurance upto USD12000 guarranteed by alibaba, which can proect your money well to ensure the lead time and products quality. (1) All products warranty is not less than one year, some models even up to two years warranty. (2) Spare parts will be provided for mass orders for customers' local maintenance. (3) Have distributors or authorized agents in main market who can provide local repair and replacement services. (4) Professional CRM management insures fast customer's enquiries and orders tracking. (5) Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility. (6) 7*24 hours online, working days respond within four hours, rest days within 12 hours.

6. Download

You can access http://www.possolution.com.cn/cn/download.html download drivers, SDK software, product specifications and user manuals.

7. Video Guide

To help customers use our products better, we have recorded and upload some video guidance, you can find them at http://www.possolution.com.cn/video.html.

8. MOQ policy

No MOQ limitation for the standard products, but the unit price is different. For customized production, you can discuss the MOQ with our sales rep.

9. Request a quote

Request a quote at http://www.possolution.com.cn/inquiry.html

Company:

OCOM Technologies Ltd. is the main supplier and manufacturer of POS and Auto-ID related products with TUV verified. OCOM is serving the fortune 500 company, and have the top 1% level trade asssurance guarrantee by alibaba.

OCOM's products portfolio covers Thermal Printer, Barcode Printer, Dot Matrix Printer, Barcode Scanner, POS Terminal, Magnetic Card Reader, Date terminal, and other POS Peripherals products(Cash Drawer,Customer Display,POS Monitor, POS keyboard,Money counter,Electronical Scale,Thermal Paper), which are widely used for retailing, restaurant, bank, lottery, transportation, logistic, and other applications. We have CE, FCC and other required certifications.

OCOM's mission is to be the compelling choice for our partners, and our three basic belief are "Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.

Contacts:

Contact: Harold Hu

OCOM Technologies Limited

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054,

China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: sales14@ocominc.com; Skype:sales14@ocominc.com MSN: ocomsales14@hotmail.com; Whatsapp: 86.18948789890;

Wechat: 18948789890(ocomsales14);

Mobile: 86.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814; Fax: 0086.755.86053207-868;