80MMThermal Printer with Auto Cutter

(Model No.: OCPP-80Y)

Features:

1. Desktop or wall-mountedtype for option.
2.Supports multi 1Dbarcodes
3.160mm/s printing speed
4.Supports 256KB NV Logostorage and 2M big buffer memory.

Technical parameters：

Printing method:	Direct thermal
Printing speed:	160mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line’s pacing :	3.75mm（Adjustable by commands）
Print command:	Compatible with the ESC/POS command
Interface type:	USB
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V（50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0～45) humidity(10～80%)（Non- condense）
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10～60℃); Humidity(10～90%)
Character size:	ANK（FontA:1.5*3.0mm/ FontB（1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA（EAN13）/JAN8（EAN8/CODE39/ITF /CODE93/CODE128
Characters:	PC347（Standard Europe）（Katakana（PC850（Multilingual）（PC860（Portuguese）（PC863 （Canadian-French）（PC865（Nordic）（West Europe（Greek（Hebrew（East Europe（Iran（WPC1252（PC866（Cyrillic#2）（PC852（Latin2）（ PC858（IranII（Latvian（Arabic（PT151（1251）
Physical characteristics：	Weight: 1.25Kg