2016 Date low cost pos terminal pocket
(M / N: P8000)

Android 4.4 operating system.

Adopts Qualcomm 1.26Hz quad-core processor.
4.0 inch IPS capacitive touch screen.

Safe and reliable design

Passed Unionpay PBOC 11& amp; amp; 12, Seizure of security certification of the past PIN.
direct connect access Unionpay POS network.

Support receipt printing and bar code reading

Support for magnetic stripe card, smart card, contactless card.

system settings	
CPU	Qualcomm quad-core 1.2GHz
BONE	Android 4.4
RAM / ROM	S12MB eMMC ROM; S12MB DDR2 RAM;
	SD card support external microphone, 32 GB maximum
Display	4.0 inch capacitive multi-touch; 480 * 800 IPS screen
Keyboard	3 Press System keys, 15 physical keys (including the power key, customized key, POS Cipher key and
	Command key)
Drums	Lithium polymer battery, 5700mAh
functional configuration	
Camera	SM AF rear camera (flashlight support), wide-angle front camera 0.3M
Printer	Integrated 2-inch thermal printer
Navigation	Integrated GPS, AGPS Support
Seeing	System indicator light, POS indicator light
Audios	Built-in speaker, buzzer, microphone, vibrator
sensors	Sensor gravity
POS	1
Payment Sound Wave	Support
magnetic strip card	MSR Triple track, bi-directional scanning ISO7811, 7812
IC Card	1 Solt, Support 1.8V / 3V / 5V, ISO7816, and PBOC EMV
Contactless card	13.56, ISO / IEC 14443 Type A / B, qPBOC
SAM Card	1 SAM Solt, 7816
key cipher	ntegrated keyboard
network settings	,
Type of network	WCDMA / GSM
Spectrum Network	WCDMA 2100MHz
	GSM / GPRS / EDGE 850/900/1800 / 1900MHz
WLAN	807.11 a / b / g / n Integrated antenna
Voice / Data Service	Support
WPAN WPAN	Bluetooth V4.0 + EDR
external interface	BIGEOGRI VALO Y EDIT
USB interface	Micro USB2.0, USB OTG Support
Jack Charger	oc Jack
lack supply	ос. учел. Радо Pin, 5V - 500mA
	Fuge Fit, 34 - Johns USB, RS232
Communication	U56, K5232
physical parameters	Loss and to the same that the
Dimensions	1 205mm * 82mm / 67mm * 33mm W D
Weight	500g (battery included)
Operating temperature	20°C - 60°C
Storage temperature	40 ° C ~ 80 ° C
Humidity	10% ~ 90% RH non-condensing
Drop test	1.0 m fall protection
Roll Drop Test	500 times
ESD protection	± contact discharge 8KV; ± 15KV air discharge
Development environment	
system environment	Android 4.4 / SP-UI
Development environment	SDK
Management software	Following PC management / MDM