

**2016 Date low cost pos terminal pocket
(M / N: P8000)**

Android 4.4 operating system.
Adopts Qualcomm 1.2GHz quad-core processor.
4.0 inch IPS capacitive touch screen.
Safe and reliable design
Passed Unionpay PBOC L1 & amp; amp; L2; Seizure of security certification of the past PIN.
direct connect access Unionpay POS network.
Support receipt printing and bar code reading
Support for magnetic stripe card, smart card, contactless card.

| | |
|--------------------------|---|
| system settings | |
| CPU | Qualcomm quad-core 1.2GHz |
| BONE | Android 4.4 |
| RAM / ROM | 512MB eMMC ROM; 512MB DDR2 RAM; SD card support external microphone, 32 GB maximum |
| Display | 4.0 inch capacitive multi-touch; 480 * 800 IPS screen |
| Keyboard | 3 Press System keys, 15 physical keys (including the power key, customized key, POS Cipher key and Command key) |
| Drums | Lithium polymer battery, 5700mAh |
| functional configuration | |
| Camera | 5M AF rear camera (flashlight support), wide-angle front camera 0.3M |
| Printer | Integrated 2-inch thermal printer |
| Navigation | Integrated GPS, AGPS Support |
| Seeing | System indicator light, POS indicator light |
| Audios | Built-in speaker, buzzer, microphone, vibrator |
| sensors | Sensor gravity |
| POS | |
| Payment Sound Wave | Support |
| magnetic strip card | MSR Triple track, bi-directional scanning ISO7811, 7812 |
| IC Card | 1 Solt, Support 1.8V / 3V / 5V, ISO7816, and PBOC EMV |
| Contactless card | 13.56, ISO / IEC 14443 Type A / B, qPBOC |
| SAM Card | 1 SAM Solt, 7816 |
| key cipher | Integrated keyboard |
| network settings | |
| Type of network | WCDMA / GSM |
| Spectrum Network | WCDMA 2100MHz GSM / GPRS / EDGE 850/900/1800 / 1900MHz |
| WLAN | 802.11 a / b / g / n Integrated antenna |
| Voice / Data Service | Support |
| WPAN | Bluetooth V4.0 + EDR |
| external interface | |
| USB interface | Micro USB2.0, USB OTG Support |
| Jack Charger | DC JACK |
| Jack supply | Pogo Pin, 5V - 500mA |
| Communication | JSB, RS232 |
| physical parameters | |
| Dimensions | H 205mm * 82mm / 67mm * 33mm W D |
| Weight | 500g (battery included) |
| Operating temperature | -20 ° C ~ 60 ° C |
| Storage temperature | -40 ° C ~ 80 ° C |
| Humidity | 10% ~ 90% RH non-condensing |
| Drop test | 1.0 m fall protection |
| Roll Drop Test | 500 times |
| ESD protection | ± contact discharge 8KV; ± 15KV air discharge |
| Development environment | |
| system environment | Android 4.4 / SP-UI |
| Development environment | SDK |
| Management software | Following PC management / MDM |