

Model	POS-1561-W	POS-1561-A
Name	15.6 inch touch POS terminal	
Housing material	Aluminium alloy Plus ABS	
Main screen	15.6 inch touch screen monitor	
Resolution	1920*1080	
Brightness	2 250cd/m	
View angle	Horizon: 170, Vertical :170	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.6 or 11.6 inch display W/ or W/o touch function for option	
MSR	3-track card reader for option	
<b>Performance</b>		
Motherboard	Intel Celeron J6412,2.0GHz or Celeron J4125,intel core th I3 / I5 11 CPU for option	Rockchip series RK3568 ,quad core 2.0G, RK3588 for option
System Memory	1*SO-DIMM DDR4 slot, support 2400mHZ, 4GB /8GB /16G for option	On board DDR4 4GB, 8G /16G for option
Storage device	64GB M.2 SSD or higer, up to 512GB	on board 32GB EMMC 64GB/128GB for option
LAN/WLAN	10/100/1000Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10/100/1000Mbs,Realtek RTL8111F Lan chip Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0
Operating System	Support Windows 10/11	Android 11
<b>Connectivity</b>		
External I/O port J6412	Power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1,USB*8,COM*2,HDMI*1	
	Line out&MIC in 2in1 JACK *1	
	Customized Type C port for second display (optional)	
External I/O port RK3568	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1,USB*6,COM*1	
	RJ11 for cash drawer*1,TF card slot*1,SIM card slot*1	
	Line out*1,MIC in*1	
Customized Type C port for second display (optional)		
<b>Environment</b>		
Operating temperature	0 to 50 degrees centigrade	
Storage temperature	-20 to 60 degrees centigrade	
Working humidity	10%~90% No condensation	
Storage humidity	10%~90% No condensation	
<b>Package</b>		
Weight	Net 6.0 Kg, Gross 7.23Kg	
Package with foam inside	436*400*166mm	
<b>Accessories</b>		
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
<b>Other</b>		

Compliance

FCC Class A/CE Mark/LVD/CCC