

10 inches Windows or Android Supported POS Terminal With Thermal Printer

(M/N:POS-B10/B10-A)

Features:

- 1 Intel Celeron Processor J1900 Quad core 2.0GHz HightConfiguration CPU for Windows system
- 1 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- 1 2GB RAM+8GB ROM standard (Android)
- 1 2GB RAM+32GB SSD standard (Windows)
- 1 Multi-point capacitive touch screen
- 1 Embedded 58mm or 80mm thermal printer(Optional)
- 1 Embedded MSR RFID reader(Optional)
- 1 Stylish display panel

Applications:

- 1 Catering: hotel, restaurant, fast-food restaurant, coffeeshop, bakery and cake shop
- 1 Retailer: Business Street, boutique, department store,cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa, night club, theme park, casino andpoint of sales for lottery ticket
- 1 Commercial: information management terminals for parking lot,inn, aviation, subway, station and wharf

Pictureshow:



Parameter:

| | |
|---------------------------|---|
| Model | POS-B10/POS-B10-A |
| Main Board① | Intel Celeron Processor J1900 Quad core 2.0GHz (Windows) |
| Main Board② | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android) |
| OS① | Windows7(Beta) |
| OS② | Android 5.1 |
| Memory① | 2GB RAM 32GB SSD (Windows) |
| Memory② | 2GB RAM 8GB ROM (Android) |
| Touch Screen | Multi-point capacitive touch |
| Screen Size | Main screen10.1 inch,Vice screen10.1inch |
| Color | Black or Wihte |
| Printer | 58mm big gear thermal printer or 80mm thermal printer with Auto cutter(Optional) |
| I/O port□□1900□ | USB*4 RJ45*1 RJ11*1 HDMI*1(for vice screen) DB9 RS232 port *1 RJ11*1 TF slot *1 RJ45*1 |
| I/O port(□A83T) | HDMI*1(for vice screen) USB*2 DB9 RS232 port*1 Audio*1 USB OTG port |
| Operating temperature | 0°C to 40°C |
| Othter Function (Andriod) | Bluetooth, WIFI,GPS |
| Optional items(Windows) | LCD VFD display,RFID,MSR cammera,3G, DB25 parallel port, DB9 RS232 port*3 Other size Screen |
| Optional items(Andriod) | 3G,cammera, LCD VFD display,RFID,MSR,Other size Screen |
| Storage temperature | -20°Cto 60°C |
| Packing dimension | 46*43*51cm |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put |

