

11.6 inches Windows or Android POS Terminal

With Thermal Printer

(M/N:POS-B11.6-W)

Features:

- l Elegant B base for pos machine.
- l Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system
- l 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- l 2GB RAM+8GB ROM standard (Android)
- l 2GB RAM+32GB SSD standard (Windows)
- l 11.6 inches Multi-point capacitive touch screen
- l 11.6 inches non-touch second screen,
- l Embedded 58mm or 80mm thermal printer(Optional)
- l Embedded MSR RFID reader(Optional)
- l Stylish display panel

Applications:

- l Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- l Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- l Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- l Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter:

Model	POS-B11.6/POS-B11.6-A
Main Board□	Intel Celeron Processor J1900 Quad core 2.0GHz (Windows)
Main Board□	2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android)
OS□	Windows7(Beta)
OS□	Android 5.1
Memory□	2GB RAM 32GB SSD (Windows)
Memory□	2GB RAM 8GB ROM (Android)
Touch Screen	Multi-point capacitive touch
Screen Size	11.6 inch,16:9
Customer Display	LCD customer display (Default), Options: 11.6inches non-touch screen, VFD customer display, Other size Scree, or non-customer display
Color	Black or White
Printer	58mm big gear thermal printer or 80mm thermal printer with Auto cutter (Options)
I/O port□□J1900□	USB*4
	RJ45*1
	RJ11*1□optional□
	VGA*1
	HDMI*1(for vice screen)
	DB9 RS232 port *1,(can add 2 ports for optional)
I/O port(□A83T)	RJ11*1 (Opional)
	TF slot *1
	RJ45*1
	HDMI*1(for vice screen)
	USB*2 (can add 4 ports for optional)
	DB9 RS232 port*1
	Audio*1
	USB OTG port*1
Operating temperature	0°C to 40°C

Other Function (Android)	Bluetooth, WIFI
Optional items(Windows)	RFID,MSR camera,3G, DB25 parallel port, DB9 RS232 port*3
Optional items(Android)	3G,4G camera, LCD VFD display,RFID,MSR,Other size Screen
Storage temperature	-20°Cto 60°C
Packing dimension	46*43*51cm
Power adapter	110-240V/50-60HZ AC power Input, 12/24V output depending on the printer





POS-B11.6





POS-B11.6





POS-B11.6



[POS-8829](#)

[POS-8912](#)