

2017 newest design all in one pos system with thermal printer

(M/N:POS-C15)

Features:

l Intel Celeron Processor J1900 Quad core 2.0GHz HighConfiguration CPU for Windows system

l 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

l 2GB RAM+8GB ROM standard (Android)

l 2GB RAM+32GB SSD standard (Windows)

l 5 wire resistive touch screen(default),Capacitivescreen for optional

l 58/80mm embedded thermal printer for optional

l Magnetic member card reader for optional

l VFD customer display or vice screen

Applications:

l Catering: hotel,restaurant, fast-food restaurant, coffee shop, bakery and cake shop

l Retailer: Business Street,boutique, department store, cosmetics shop and high-class barbershop

l Recreation: sauna, spa,night club, theme park, casino and point of sales for lottery ticket

l Commercial: informationmanagement terminals for parking lot, inn, aviation, subway, station and wharf

Pictureshow:



Parameter

Model	POS-C15
Color	Silver-gray or Black
CPU□	Intel Celeron J1900 Quad core 2.0 GHZ
CPU□	2.0GHz A83T ARM 8-Core Cortex-A7 Processor
Memory□	DDRIII 1066/1333*1 2GB (default) (Windows)
Memory□	2GB RAM 8GB ROM □Android□

OS	Windows7(Beta)	
OS	Android 5.1	
Hard Driver	SSD 32GB (default) (Windows)	
LCD panel Size	15 inch TFT LCD	
Brightness	350cd/m2	
Resolution	1024*768(max)	
Touch Screen	5 wire resistive touch screen	
Printer Parameter	Print Density	203dpi
	Printing Command	ESC/POS
	Paper Roll Diameter	60mm
	Paper Width	58mm or 80mm
	Printing Speed	60mm/s or 150mm/s
	MCBF(life)	50km
Other optinoal funtion	MSR/ VFD220 customer displiay/ vice screen	
View Angle	Horizon: 150; Vertical :140	
I/O port	1* power button 12V DC in jack*1	
	HDMI*1	
	VGA(15Pin D-sub)*1	
	LAN:RJ-45*1	
	USB(2.0)*4	
	RS232*2	
	MIC IN*1 Audio out*1	
I/O port	RJ11*1 (Optional)	
	TF slot *1	
	RJ45*1	
	HDMI for vice screen	
	DB9 RS232 port*1	
	USB*2	
Audio*1		
Operating temperature	0°C to 40°C	
Storage temperature	-20°Cto 60°C	
Operating System	Windows XP above, Embedded,WEPOS,Linux	
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put	