

Portable handheld laser wireless barcode scanner RF433MHZ or bluetooth

(M / N: OCBS-W011)

Product Description

Bluetooth barcode scanner feature:

- 1) Wireless laser barcode scanner RF 433MHZ (OCBS-W011A) or Bluetooth(OCBS-W011B) for option
- 2) High scan rate (100 scans / sec) and long reading distance;
- 3) Excellent decode capability;
- 4) Durable construction combined with future-proofing;
- 5) Grey and Black Color available

Wireless Bluetooth Barcode Scanner specification:

Performance Characteristics	
Wireless Frequency	433MHZ or Bluetooth
Transmission distance	300M in open area (433MHZ); 15M (bluetooth)
Storage	400,000 barcode (433MHZ); 2000 barcode (bluetooth)
Light Source:	Visible laser (650-670nm)
Scan Rate:	200 scans per second
Reading Distance	2.5 ~ 600mm (100% UPC / EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, Minimum reflective difference (@ 650nm)
Error Rate:	1/3000000
Decode Capability:	UPC / EAN, UPC / EAN with supplementals, UCC / EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI , code 11, ATA, RSS variants, Chinese 2 of 5 ...
Physical Characteristics	
Interfaces Supported:	433MHz or Bluetooth Wireless communication, 433 version has a USB receiver, USB port for battery charging
Battery	900mAh, 3.3V
Working Current:	15 to 30 mA
Standby Current:	18uA ~ 5mA
Power:	5V, 500mA
Scanning Angle	Inclination 45 ° Elevation 60 °
Dimensions:	L165mm X W63mm X H87mm

Weight:	129g (without stand)
Stand	Optional
Color:	Grey or black
User Environment	
Operating Temperature:	0~40 deg C
Storage Temperature:	-40~ 60 deg C
Humidity:	5 ~ 95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/- 15KV air discharge and +/- 8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI / RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product