Warehouse Handheld Laser Barcode Scanner Machine (Model: OCBS-L008)

Specification:

Specification:				
Performance Characteristics	S			
Light Source:	Visible laser (650-670nm)			
Scan Rate:	100 scans per second			
Reading Distance	2.5 ~600mm (100% UPC/EAN)			
Scanner Type:	Bi-directional			
Resolution:	0.10mm (4mil) at PCS 0.9			
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)			
Decode Capability:	UPC/EAN, UPC/EAN with supplemental, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, coda bar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5			
Physical Characteristics				
Interfaces Supported:	PS2, RS232, USB			
Voltage:	DC+5V+/-5%			
Current:	100 mA			
Idle Current:	<40 mA			
Power Source:	Host power or external (RS232) power supply			
Scanning Angle	Inclination 45° Elevation 60°			
Dimensions:	L165.42mm X W69.72mm X H89.67mm			
Weight:	140g (without stand)			
Stand	Optional			
Color:	lvory and black			
User Environment				
Operating Temperature:	0 Degree C~50 Degree C			
Storage Temperature:	-40 Degree C~ 70 Degree C			
Humidity:	5~95% relative humidity, non-condensing			
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge			
Drop Specifications:	Withstands multiple 1.5m drops to concrete			
Safe:				
EMI/RFI:	FCC Class A and CE			
Laser Safety:	CDRH class 2 laser product			

Product Details:



Product Picture





Features





Excellent decode capability;







Durable construction combined with future-proofing;



All-round show





Parameter

Performance Characteris	tics		
Light Source:	Visible laser (650-670nm)		
Scan Rate:	100 scans per second		
Reading Distance	2.5 ~600mm (100% UPC/EAN)		
Scanner Type:	Bi-directional Bi-directional		
Resolution:	0.10mm (4mil) at PCS 0.9		
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)		
Decode Capability:	UPC/EAN, UPC/EAN with supplemental, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, coda bar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5		
Physical Characteristics			
Interfaces Supported:	PS2. RS232, USB		

Voltage:	DC+5V+/-5%	
Current:	100 mA	
Idle Current:	<40 mA	
Power Source:	Host power or external (RS232) power supply	
Scanning Angle	Inclination 45° Elevation 60°	
Dimensions:	L165.42mm X W69.72mm X H89.67mm	
Weight:	140g (without stand)	
Stand	Optional	
Color:	Ivory and black	
User Environment		
Operating Temperature:	0 Degree C~50 Degree C	
Storage Temperature:	rage Temperature: -40 Degree C~ 70 Degree C	
Humidity:	5~95% relative humidity, non-condensing	
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge	
Drop Specifications:	Withstands multiple 1.5m drops to concrete	
Safe:		
EMI/RFI;	FCC Class A and CE	
	CDRH class 2 laser product	
Laser Safety:	CDRH class 2 laser product	

Production Line





Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
1	Thermal Printer	40,000 Sets / Month	250,000 Sets
1	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
1	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
1	Barcode Scanner	40,000 Sets / Month	20,000 Sets
1	POS Machine	5,000 Sets / Month	10,000 Sets
1	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

√ Indicates information has been verifed onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products



have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
1	Ageing Tester	No Information	6
1	Withstand Voltage Tester	CC2670A	1
1	Oscilloscope	TBS1102	1
1	DC Power Supply	PS-305DM	6
1	Digital Torque Meter	HP100	077
4	Calliper	GUANGLU	2
1	Multi-meter	VC890D	7
1 3	Test Computer	No Information	13

7

→ Indicates information has been verifed onsite by IUV on 2013.7.15

Certifications



Packing and Shipment





Payment

















Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand,

and we have estabilshed goods relationship with our customers and have friendly communication with each other.



Why you choose us?





Flexible Cooperation

Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust









OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Websites: http://www.possolution.com.cn; http://www.ocominc.com;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637,190852203; Tel/Fax: +86.755.8605.3207.



Relevant documents:

Do you want to know more product information?Please Click here.

▼

Specification User's Manual