cheap 58mm POS58 thermal pos printer

(OCPP-58E)



ProductIntroduction:

OCPP-58E is a well-designed economic printerfor common thermal bill printing ,this mold is with solid material, Exquisiteworkmanship. Transparent cover design, simple and fashion, easy for users toknow the paper rolls' Using status, OCPP-58E adopt built-in power supply, notonly can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

pos printer,58mm thermal printer,pos receipt printer

ProductFeatures□

- •Simple and fashion, With solid material, exquisitework manship.
- Easy paper install structure, simple and convenient tooperate
- •Built-in power supply design, to save space and more convenient to configure;
- •Transparent cover design, the user can know the paperroll's using status anytime;
- ●Support GB18030 big font, easy to print uncommoncharacters
- •Support multi language print, suitable for users all over theworld;
- •Support download and print LOGO&graphics;
- •Support Windows, Linux, Android and IOS system printing

ApplicationArea

Shoppingmalls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items		Parameters
Print parameters		Thermal Line
		HIMM
	Resolution	384dots/Line[18dots/mm[7203dpif]
		90mm/Second
	Interface Type	USB/USB+Bluetooth
		3.75 mm[Can adjust line spacing by command[
		Font A:32 character /Line
		Font B:42 character/Line
		Simple, traditional Chinese-16 lines
		Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter[]Font A]1.5×3.0mm[12×24dots[
		Font B[]1.1×2.1mm[]9×17dots[] Simplified/Traditional Chinese[]3.0×3.0mm[24×24 dots[]
	Extended	PC437/Katakana/PC850/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Character	character set	
		UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/
		CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
	T	Thermal Roll
Paper		
		77.54.0 Smm 500mm
		Soumm Soumm Easy feed(Clameshell feed)
Print		Easy read(Lamesheu reed) ESC/POS
commands	Commanus	ESUPUS
Power	Power Adaptor	input/IAC 100V-240V,50-60Hz
1000	ower rauptor	DubutIDC 12V/CA
	output	
Buffer		ik
1		40K

physical	Weight	590g
characteristics	Dimension	185*130*112(MM)
Environment	Working	Temp[]5 \sim 45°C] Humidity[]10 \sim 80%
	Storage	Temp[-10 ~ 50℃ [Humidity[10 ~ 90%]No dew[]
Reliability	Print Head Life	50KM[print density≤12.5[]
parameter		



