

handheld android pos terminal machine with NFC and thermal printer

(M/N:Z90)

Keywords

android pos terminal,handheld pos terminal,android pos

Feature:

l Android 4.4 or 5.1 operating system

l 5.0 inch screen touch

l Long standby battery capacity is 3600 mAh

l 58mm thermal printer

l 5 million pixels camera

l 2G /3G/4G wifi, bluetooth communication(4Goptional),

l Integrated magnetic card reader,induction ICcard reader and contact IC card reader

l Passed the EMV L1 L2and PBOC bank paymentcertification

l Thecradle can be used for communication, charging, power bank,and providingwireless network (Optional)

Application :

applychain supermarkets, restaurants, convenience stores, clothing store, premises, bakery, cashier, pay, enters sells saves the businessmanagement function.

TechnicalSpecification:

Basic Information	
Operating system	Android 4.4 or 5.1
RAM	RAM:1GB
Extended stored	FLASH:8GB
Display screen	5.0 inch
Touch screen	Capacitive touch screen, support the electronic signature
Battery	Lithium battery3600 mah, 3.7 V
Bluetooth	Bluetooth 4.0
Camera	5 mega-pixel camera
Positioning function	GPS AGPS WLAN for Positioning
Printer	58mm thermal printer 30mm diameter Paper roll
Interface	Micro USB
POS Function	
Magnetic card reader	Full track magnetic card reader Support ISO1788/7812,AAMVA protocol

IC card read-write	Support ISO7816 protocol
Non-contact card reader	Support ISO/IEC 14443 Type A&B, Mifare, felica card, in line with the EMV/PBOC PAYPASS specification
PSAM Card	Bank security payment chip card
Certification	Unionpay card acceptance terminal network detection EMV/PBOC3.0 L1 and L2 certification EMV/qPBOC3.0 L1 and L2 certification Unionpay intelligent safety standards point-of-sale terminals
Network Parameters	
Network Type	GSM,WCDMA,TD-SCDMA,FDD-LTE,TDD-LTE
Network Spectrum	GSM850/900/1800/1900
	WCDMA2100/1900/900/850
	TD-SCDMA B34/B39
	FDD-LTE B1/B2/B3/B4/B5/B7/B8/B20
	TDD-LTE B38/B39/B40/B41
WLAN	IEEE802.11.b/n/g
Physical Parameters	
Size	191mm×80mm×46mm
Weight	650g
Operating Temp	-20°C ~ 60°C
Storage Temp	-40°C ~ 80°C
Humidity	10%~90% RH non-condensing